

77061121 Information

Part Number 77061121

Manufacturer CTS Resistor Products

Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 5 RES 120 OHM 6SIP

Package 6-SIF

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









77061121 Specifications

Manufacturer Part Number Manufacturer Category Resistors Resistor Networks, Arrays Package 6-SIP Series 770 Circuit Type Bussed Resistance (Ohms) 120 Tolerance ±2% Number of Resistors 5 Number of Pins 6 Power Per Element 100mW Temperature Coefficient Operating Temperature -55°C ~ 125°C Applications Mounting Type Through Hole Package / Case Supplier Device Package Size / Dimensions 0 600% Universions		
Category Resistor Networks, Arrays Package 6-SIP Series 770 Circuit Type Bussed Resistance (Ohms) 120 Tolerance ±2% Number of Resistors 5 Number of Pins 6 Power Per Element 100mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP	Manufacturer Part Number	77061121
Resistor Networks, Arrays Package 6-SIP Series 770 Circuit Type Bussed Resistance (Ohms) 120 Tolerance ±2% Number of Resistors 5 Number of Pins 6 Power Per Element 100mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP	Manufacturer	CTS Resistor Products
Package 6-SIP Series 770 Circuit Type Bussed Resistance (Ohms) 120 Tolerance ±2% Number of Resistors 5 Number of Pins 6 Power Per Element 100mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP	Category	Resistors
Series 770 Circuit Type Bussed Resistance (Ohms) 120 Tolerance ±2% Number of Resistors 5 Number of Pins 6 Power Per Element 100mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP		Resistor Networks, Arrays
Circuit Type Bussed Resistance (Ohms) 120 Tolerance ±2% Number of Resistors 5 Number of Pins 6 Power Per Element 100mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP	Package	6-SIP
Resistance (Ohms) 120 Tolerance ±2% Number of Resistors 5 Number of Pins 6 Power Per Element 100mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP	Series	770
Tolerance ±2% Number of Resistors 5 Number of Pins 6 Power Per Element 100mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP	Circuit Type	Bussed
Number of Resistors5Number of Pins6Power Per Element100mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeThrough HolePackage / Case6-SIPSupplier Device Package6-SIP	Resistance (Ohms)	120
Number of Pins 6 Power Per Element 100mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP	Tolerance	±2%
Power Per Element 100mW Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP	Number of Resistors	5
Temperature Coefficient $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Applications $-$ Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP	Number of Pins	6
Operating Temperature -55°C ~ 125°C Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP	Power Per Element	100mW
Applications - Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP	Temperature Coefficient	±100ppm/°C
Mounting Type Through Hole Package / Case 6-SIP Supplier Device Package 6-SIP	Operating Temperature	-55°C ~ 125°C
Package / Case 6-SIP Supplier Device Package 6-SIP	Applications	-
Supplier Device Package 6-SIP	Mounting Type	Through Hole
	Package / Case	6-SIP
Circ / Dimension 0.600" I. v. 0.000" W (15.24mm v. 2.50mm)	Supplier Device Package	6-SIP
Size / Difficultion U.000 L x 0.098 W (15.24mm x 2.50mm)	Size / Dimension	0.600" L x 0.098" W (15.24mm x 2.50mm)
Height - Seated (Max) 0.195" (4.95mm)	Height - Seated (Max)	0.195" (4.95mm)
Report errors?		Report errors?

77061121 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

77061121 Payment Methods





















77061121 Shipping Methods













If you have any question about 77061121, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com