

### **7940008171 Information**



For Reference Only

Part Number 7940008171 Manufacturer Weidmuller Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 4PDT 6A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 7940008171 Specifications

Manufacturer Part Number         7940008171           Manufacturer         Weidmuller           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         RCM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         41.6mA           Coil Voltage         24V AC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         6A           Switching Voltage         250V AC - Max           Turn On Voltage (Max)         19.2 V AC           Turn Off Voltage (Min)         7.2 V AC           Operate Time         15ms           Release Time         10ms           Features         Test Button           Mounting Type         Socketable           Termination Style         Plug In, Quick Connect - 0.110" (2.8mm)		
CategoryRelaysPackage-SeriesRCMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current41.6mACoil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm)	Manufacturer Part Number	7940008171
Package - Series RCM Relay Type General Purpose Coil Type Non Latching Coil Current 41.6mA Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Manufacturer	Weidmuller
Package         -           Series         RCM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         41.6mA           Coil Voltage         24VAC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         6A           Switching Voltage         250VAC - Max           Turn On Voltage (Max)         19.2 VAC           Turn Off Voltage (Min)         7.2 VAC           Operate Time         15ms           Release Time         10ms           Features         Test Button           Mounting Type         Socketable           Termination Style         Plug In, Quick Connect - 0.110" (2.8mm)	Category	Relays
SeriesRCMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current41.6mACoil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm)		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current41.6mACoil Voltage24V ACContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage250V AC - MaxTurn On Voltage (Max)19.2 V ACTurn Off Voltage (Min)7.2 V ACOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm)	Package	-
Coil TypeNon LatchingCoil Current41.6mACoil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm)	Series	RCM
Coil Current 41.6mA Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Relay Type	General Purpose
Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 6A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 19.2 VAC  Turn Off Voltage (Min) 7.2 VAC  Operate Time 15ms  Release Time 10ms  Features Test Button  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Coil Current	41.6mA
Contact Rating (Current)  Switching Voltage  250VAC - Max  Turn On Voltage (Max)  19.2 VAC  Turn Off Voltage (Min)  7.2 VAC  Operate Time  15ms  Release Time  10ms  Features  Test Button  Mounting Type  Socketable  Termination Style  Plug In, Quick Connect - 0.110" (2.8mm)	Coil Voltage	24VAC
Switching Voltage 250VAC - Max  Turn On Voltage (Max) 19.2 VAC  Turn Off Voltage (Min) 7.2 VAC  Operate Time 15ms  Release Time 10ms  Features Test Button  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  19.2 VAC  Turn Off Voltage (Min)  7.2 VAC  Operate Time  15ms  Release Time  10ms  Features  Test Button  Mounting Type  Socketable  Termination Style  Plug In, Quick Connect - 0.110" (2.8mm)	Contact Rating (Current)	6A
Turn Off Voltage (Min)  7.2 VAC  Operate Time  15ms  Release Time  10ms  Features  Test Button  Mounting Type  Socketable  Termination Style  Plug In, Quick Connect - 0.110" (2.8mm)	Switching Voltage	250VAC - Max
Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Turn On Voltage (Max)	19.2 VAC
Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Turn Off Voltage (Min)	7.2 VAC
Features Test Button  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Operate Time	15ms
Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Release Time	10ms
Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Features	Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, Quick Connect - 0.110" (2.8mm)
		Report errors?

### 7940008171 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 7940008171 Payment Methods



















## 7940008171 Shipping Methods













If you have any question about 7940008171, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com