

**794664-8 Information**


For Reference Only

**Part Number** [794664-8](#)  
**Manufacturer** TE Connectivity AMP Connectors  
**Category** Connectors, Interconnects  
[Rectangular Connectors - Headers, Male Pins](#)  
**Description** CONN HEADER VERT 8POS TIN  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



Request a Quote

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**794664-8 Specifications**

|                            |                                                                                          |
|----------------------------|------------------------------------------------------------------------------------------|
| Manufacturer Part Number   | <a href="#">794664-8</a>                                                                 |
| Manufacturer               | TE Connectivity AMP Connectors                                                           |
| Category                   | Connectors, Interconnects<br><a href="#">Rectangular Connectors - Headers, Male Pins</a> |
| Package                    | -                                                                                        |
| Series                     | AMP-DUAC                                                                                 |
| Connector Type             | Header                                                                                   |
| Contact Type               | Male Pin                                                                                 |
| Pitch - Mating             | 0.165" (4.20mm)                                                                          |
| Style                      | Board to Board or Cable                                                                  |
| Shrouding                  | Shrouded - 4 Wall                                                                        |
| Number of Positions        | 8                                                                                        |
| Number of Positions Loaded | All                                                                                      |
| Number of Rows             | 2                                                                                        |
| Row Spacing - Mating       | 0.165" (4.20mm)                                                                          |
| Mounting Type              | Through Hole                                                                             |
| Termination                | Solder                                                                                   |
| Fastening Type             | Locking Ramp                                                                             |
| Contact Length - Mating    | -                                                                                        |
| Contact Length - Post      | 0.138" (3.50mm)                                                                          |
| Overall Contact Length     | -                                                                                        |
| Insulation Height          | 0.504" (12.80mm)                                                                         |
| Contact Shape              | Square                                                                                   |
| Contact Finish - Mating    | Tin-Lead                                                                                 |

|                                   |                                |
|-----------------------------------|--------------------------------|
| Contact Finish Thickness - Mating | 118.1µin (3.00µm)              |
| Contact Finish - Post             | Tin-Lead                       |
| Contact Material                  | Copper Alloy                   |
| Insulation Material               | Polyamide (PA), Nylon          |
| Features                          | -                              |
| Operating Temperature             | -55°C ~ 105°C                  |
| Ingress Protection                | -                              |
| Material Flammability Rating      | UL94 V-2                       |
| Insulation Color                  | Natural                        |
|                                   | <a href="#">Report errors?</a> |

## 794664-8 Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 794664-8 Payment Methods



## 794664-8 Shipping Methods



If you have any question about 794664-8, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)