



7M-14.7456MAAE-T Information

Part Number 7M-14.7456MAAE-T Manufacturer TXC CORPORATION

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 14.7456MHZ 12PF SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7M-14.7456MAAE-T Specifications

Manufacturer Part Number7M-14.7456MAAE-TManufacturerTXC CORPORATIONCategoryCrystals, Oscillators, ResonatorsPackage4-SMD, No LeadSeries7MTypeMHz CrystalFrequency14.7456MHzFrequency Stability±30ppmFrequency Tolerance±30ppmLoad Capacitance12pFESR (Equivalent Series Resistance)100 OhmOperating ModeFundamentalOperating Temperature-20°C ~ 70°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.031" (0.80mm)	*	
Category Crystals Package 4-SMD, No Lead Series 7M Type MHz Crystal Frequency 14.7456MHz Frequency Stability ±30ppm Frequency Tolerance ±30ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Pundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension Height - Seated (Max) Crystals ON Head Crystals 17 A-SMD, No Lead Size / Dimension 0.031" (0.80mm)	Manufacturer Part Number	7M-14.7456MAAE-T
Package 4-SMD, No Lead Series 7M Type MHz Crystal Frequency 14.7456MHz Frequency Stability ±30ppm Frequency Tolerance ±30ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)	Manufacturer	TXC CORPORATION
Package 4-SMD, No Lead Series 7M Type MHz Crystal Frequency 14.7456MHz Frequency Stability ±30ppm Frequency Tolerance ±30ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)	Category	Crystals, Oscillators, Resonators
Series 7M Type MHz Crystal Frequency 14.7456MHz Frequency Stability ±30ppm Frequency Tolerance ±30ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)		Crystals
Type MHz Crystal Frequency 14.7456MHz Frequency Stability ±30ppm Frequency Tolerance ±30ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)	Package	4-SMD, No Lead
Frequency Stability ±30ppm Frequency Tolerance ±30ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)	Series	7M
Frequency Stability ±30ppm Frequency Tolerance ±30ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)	Туре	MHz Crystal
Frequency Tolerance ±30ppm Load Capacitance 12pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)	Frequency	14.7456MHz
Load Capacitance 12pF ESR (Equivalent Series Resistance) 100 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)	Frequency Stability	±30ppm
ESR (Equivalent Series Resistance) Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)	Frequency Tolerance	±30ppm
$\begin{array}{llllllllllllllllllllllllllllllllllll$	Load Capacitance	12pF
Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)	ESR (Equivalent Series Resistance)	100 Ohm
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)	Operating Mode	Fundamental
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)	Operating Temperature	-20°C ~ 70°C
Package / Case 4-SMD, No Lead Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)	Ratings	-
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) 0.031" (0.80mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.031" (0.80mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Report errors?	Height - Seated (Max)	0.031" (0.80mm)
		Report errors?

7M-14.7456MAAE-T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7M-14.7456MAAE-T Payment Methods



















7M-14.7456MAAE-T Shipping Methods













If you have any question about 7M-14.7456MAAE-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com