

8002-12-00 Information



For Reference Only

Part Number 8002-12-00 Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED DPST 500MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









8002-12-00 Specifications

Manufacturer Part Number 8002-12-00 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 8000 Relay Type Reed Coil Type Non Latching Coil Current 24mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms
Category Relays Signal Relays, Up to 2 Amps Package - Series 8000 Relay Type Reed Coil Type Non Latching Coil Current 24mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC
Package - Series 8000 Relay Type Reed Coil Type Non Latching Coil Current 24mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC
Package - Series 8000 Relay Type Reed Coil Type Non Latching Coil Current 24mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC
Series 8000 Relay Type Reed Coil Type Non Latching Coil Current 24mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC
Relay Type Coil Type Non Latching Coil Current 24mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC
Coil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDC
Coil Current 24mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC
Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC
Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC
Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC
Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC
Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC
Turn Off Voltage (Min) 1 VDC
Operate Time 0.5ms
Release Time 0.5ms
Features -
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

8002-12-00 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

8002-12-00 Payment Methods





















8002-12-00 Shipping Methods













If you have any question about 8002-12-00, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com