

800NH4AG

800NH4AG Information

Heisener.com	Part Number Manufacturer Category Description Package	800NH4AG Eaton Circuit Protection Electrical, Specialty Fuses FUSE SQ 800A 500VAC RECTANGULAR Rectangular, Blade For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



800NH4AG Specifications

Manufacturer Part Number800NH4AGManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating800AVoltage Rating - ACS00VVoltage Rating - ACSoloVApplicationsFactical, IndustrialApplicationsElectrical, IndustrialApprovalsNHApprovalsCE VDEOrenting Temperature-Approvals210AAApprovals120AAAponting Type-Auting Type <th></th> <th></th>		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating800AVoltage Rating - AC500VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseSa00°, Sa00°, Sa00°	Manufacturer Part Number	800NH4AG
FunctionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating800AVoltage Rating - AC500VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialPeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature120kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating800AVoltage Rating - AC500VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension3.00" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating800AVoltage Rating - AC500VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesNHClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseSa30" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingSto0AVoltage Rating - ACSto0VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialPeaturesIndicatingVoltage Rating Capacity @ Rated Notage-ApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseScorng Lange Stated Stat	Package	Rectangular, Blade
Current Rating800AVoltage Rating - AC500VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Series	-
Voltage Rating - AC500VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature120kABreaking Capacity @ Rated VoltageHolderPackage / CaseRectangular, BladeSize / Dimension3.007" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Fuse Type	Square
Voltage Rating - DC.Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature.Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Current Rating	800A
Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseRectangulandSize / Dimension3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Voltage Rating - AC	500V
ApplicationsElectrical, IndustrialApplicationsIndicatingFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseRectangulang BadeSize / Dimension3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Response Time	Fast
ClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Applications	Electrical, Industrial
ApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Class	NH
Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Approvals	CE, VDE
Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Breaking Capacity @ Rated Voltage	120kA
Size / Dimension 3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
	Size / Dimension	3.307" L x 3.425" W x 4.094" H (84.00mm x 87.00mm x 104.00mm)
Report er		Report errors?

800NH4AG Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 800NH4AG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com