

801-83-024-65-410101 Information



For Reference Only

Part Number 801-83-024-65-410101

Manufacturer Preci-Dip

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description PCB CONN PRESS FIT 2.54MM

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









801-83-024-65-410101 Specifications

Manufacturer Part Number 801-83-024-65-410101 Manufacturer Preci-Dip Category Connectors, Interconnects Package - Series 801 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.276" (7.00mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -55°C ~ 125°C		
Category Connectors, Interconnects Package - Series 801 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.276" (7.00mm) Contact Length - Post 0.110" (2.79mm)	Manufacturer Part Number	801-83-024-65-410101
Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series 801 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height Contact Length - Post 0.110" (2.79mm)	Manufacturer	Preci-Dip
Package - Series 801 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.276" (7.00mm) Contact Length - Post 0.110" (2.79mm)	Category	Connectors, Interconnects
Series 801 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.276" (7.00mm) Contact Length - Post 0.110" (2.79mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Socket Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded Pitch - Mating Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish - Mating Insulation Color Black Insulation Height Contact Length - Post On 110" (2.79mm)	Package	-
Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.276" (7.00mm) Contact Length - Post 0.110" (2.79mm)	Series	801
StyleBoard to BoardNumber of Positions24Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.276" (7.00mm)Contact Length - Post0.110" (2.79mm)	Connector Type	Socket
Number of Positions Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Insulation Height O.276" (7.00mm) Contact Length - Post 0.110" (2.79mm)	Contact Type	Female Socket
Number of Positions Loaded Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.276" (7.00mm) Contact Length - Post O.110" (2.79mm)	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.276" (7.00mm)Contact Length - Post0.110" (2.79mm)	Number of Positions	24
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.276" (7.00mm)Contact Length - Post0.110" (2.79mm)	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.276" (7.00mm)Contact Length - Post0.110" (2.79mm)	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.276" (7.00mm)Contact Length - Post0.110" (2.79mm)	Number of Rows	1
Termination Press-Fit, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5μin (0.75μm) Insulation Color Black Insulation Height 0.276" (7.00mm) Contact Length - Post 0.110" (2.79mm)	Row Spacing - Mating	-
Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.276" (7.00mm) Contact Length - Post 0.110" (2.79mm)	Mounting Type	Through Hole
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.276" (7.00mm) Contact Length - Post 0.110" (2.79mm)	Termination	Press-Fit, Solder
Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.276" (7.00mm) Contact Length - Post 0.110" (2.79mm)	Fastening Type	Push-Pull
Insulation Color Insulation Height O.276" (7.00mm) Contact Length - Post 0.110" (2.79mm)	Contact Finish - Mating	Gold
Insulation Height 0.276" (7.00mm) Contact Length - Post 0.110" (2.79mm)	Contact Finish Thickness - Mating	29.5μin (0.75μm)
Contact Length - Post 0.110" (2.79mm)	Insulation Color	Black
•	Insulation Height	0.276" (7.00mm)
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Length - Post	0.110" (2.79mm)
	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

801-83-024-65-410101 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

801-83-024-65-410101 Payment Methods



















801-83-024-65-410101 Shipping Methods













If you have any question about 801-83-024-65-410101, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com