

### 801-87-045-10-101101 Information

contracts ener, com

For Reference Only

**Part Number** 801-87-045-10-101101

Manufacturer Preci-Dip

**Category** Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** PCB CONN SOLDER TAIL

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 801-87-045-10-101101 Specifications

Manufacturer Part Number         801-87-045-10-101101           Manufacturer         Preci-Dip           Category         Connectors, Interconnects           Package         -           Series         801           Connector Type         Socket           Contact Type         Female Socket           Style         Board to Board           Number of Positions         23           Number of Positions Loaded         All           Pitch - Mating         0.200" (5.08mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         Flash           Insulation Color         Black           Insulation Height         0.276" (7.00mm)           Contact Length - Post         0.118" (3.00mm)           Operating Temperature         -55°C ~ 125°C           Material Flammability Rating         UL94 V-0		
Category         Connectors, Interconnects           Package         -           Series         801           Connector Type         Socket           Contact Type         Female Socket           Style         Board to Board           Number of Positions         23           Number of Positions Loaded         All           Pitch - Mating         0.200" (5.08mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         Flash           Insulation Color         Black           Insulation Height         0.276" (7.00mm)           Contact Length - Post         0.118" (3.00mm)           Operating Temperature         -55°C ~ 125°C	Manufacturer Part Number	801-87-045-10-101101
Rectangular Connectors - Headers, Receptacles, Female Sockets  Package Series 801 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 23 Number of Positions Loaded All Pitch - Mating 0.200" (5.08mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.276" (7.00mm) Contact Length - Post 0.118" (3.00mm) Coperating Temperature	Manufacturer	Preci-Dip
Package         -           Series         801           Connector Type         Socket           Contact Type         Female Socket           Style         Board to Board           Number of Positions         23           Number of Positions Loaded         All           Pitch - Mating         0.200" (5.08mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         Flash           Insulation Color         Black           Insulation Height         0.276" (7.00mm)           Contact Length - Post         0.118" (3.00mm)           Operating Temperature         -55°C ~ 125°C	Category	Connectors, Interconnects
Series         801           Connector Type         Socket           Contact Type         Female Socket           Style         Board to Board           Number of Positions         23           Number of Positions Loaded         All           Pitch - Mating         0.200" (5.08mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         Flash           Insulation Color         Black           Insulation Height         0.276" (7.00mm)           Contact Length - Post         0.118" (3.00mm)           Operating Temperature         -55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions23Number of Positions LoadedAllPitch - Mating0.200" (5.08mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.276" (7.00mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions23Number of Positions LoadedAllPitch - Mating0.200" (5.08mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.276" (7.00mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-55°C ~ 125°C	Series	801
Style Board to Board  Number of Positions 23  Number of Positions Loaded All  Pitch - Mating 0.200" (5.08mm)  Number of Rows 1  Row Spacing - Mating -  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating Flash  Insulation Color Black  Insulation Height 0.276" (7.00mm)  Contact Length - Post 0.118" (3.00mm)  Operating Temperature -55°C ~ 125°C	Connector Type	Socket
Number of Positions 23  Number of Positions Loaded All  Pitch - Mating 0.200" (5.08mm)  Number of Rows 1  Row Spacing - Mating -  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating Flash  Insulation Color Black  Insulation Height 0.276" (7.00mm)  Contact Length - Post 0.118" (3.00mm)  Operating Temperature -55°C ~ 125°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.200" (5.08mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.276" (7.00mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board
Pitch - Mating0.200" (5.08mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.276" (7.00mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-55°C ~ 125°C	Number of Positions	23
Number of Rows  Row Spacing - Mating  Mounting Type  Through Hole  Termination  Solder  Fastening Type  Push-Pull  Contact Finish - Mating  Gold  Contact Finish Thickness - Mating  Insulation Color  Black  Insulation Height  0.276" (7.00mm)  Contact Length - Post  0.118" (3.00mm)  Operating Temperature	Number of Positions Loaded	All
Row Spacing - Mating  Mounting Type  Through Hole  Termination  Solder  Fastening Type  Push-Pull  Contact Finish - Mating  Gold  Contact Finish Thickness - Mating  Insulation Color  Black  Insulation Height  0.276" (7.00mm)  Contact Length - Post  0.118" (3.00mm)  Operating Temperature  -55°C ~ 125°C	Pitch - Mating	0.200" (5.08mm)
Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating Flash  Insulation Color Black  Insulation Height 0.276" (7.00mm)  Contact Length - Post 0.118" (3.00mm)  Operating Temperature -55°C ~ 125°C	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.276" (7.00mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -55°C ~ 125°C	Row Spacing - Mating	-
Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating Flash  Insulation Color Black  Insulation Height 0.276" (7.00mm)  Contact Length - Post 0.118" (3.00mm)  Operating Temperature -55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - Mating Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.276" (7.00mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating Flash Insulation Color Black Insulation Height 0.276" (7.00mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.276"$ ( $7.00mm$ )Contact Length - Post $0.118"$ ( $3.00mm$ )Operating Temperature $-55^{\circ}$ C ~ $125^{\circ}$ C	Contact Finish - Mating	Gold
Insulation Height $0.276" (7.00 \text{mm})$ Contact Length - Post $0.118" (3.00 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	Flash
Contact Length - Post $0.118'' (3.00 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.276" (7.00mm)
	Contact Length - Post	0.118" (3.00mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

### 801-87-045-10-101101 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 801-87-045-10-101101 Payment Methods



















### 801-87-045-10-101101 Shipping Methods













If you have any question about 801-87-045-10-101101, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com