

801-93-020-10-002000

801-93-020-10-002000 Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



801-93-020-10-002000 Specifications

Manufacturer Part Number801-93-020-10-002000ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series801Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions20Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - MatingSolderTerminationSolderFastening TypePush-PullContact Finish - MatingGold		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series801Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions20Number of Positions LoadedAllPitch - Mating1Number of Rows1Row Spacing - Mating-Mounting TypeSolderFerninationSolderForminationSolderForminationSolderForminationGold	Manufacturer Part Number	801-93-020-10-002000
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series801Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions20Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFeastening TypeGold	Manufacturer	Mill-Max Manufacturing Corp.
Package-Series801Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions20Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFerminationSolderFastening TypeGold	Category	Connectors, Interconnects
Series801Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions20Number of Positions LoadedAllPitch - Mating0.100"(2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFerminationSolderFastening TypeGudGotact Finish - MatingGota		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions20Number of Positions LoadedAllPitch - Mating0.100"(2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeSolderFerminationSolderFastening TypeGoldContact Finish - MatingGold	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions20Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGold	Series	801
StyleBoard to BoardNumber of Positions20Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGold	Connector Type	Receptacle
Number of Positions20Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGold	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGold	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGold	Number of Positions	20
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGold	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGold	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGold	Number of Rows	1
TerminationSolderFastening TypePush-PullContact Finish - MatingGold	Row Spacing - Mating	-
Fastening TypePush-PullContact Finish - MatingGold	Mounting Type	Through Hole
Contact Finish - Mating Gold	Termination	Solder
	Fastening Type	Push-Pull
Contact Finish Thickness - Mating 30uin (0.76um)	Contact Finish - Mating	Gold
connect ministration in a comment of the comment of	Contact Finish Thickness - Mating	30µin (0.76µm)
Insulation Color Black	Insulation Color	Black
Insulation Height 0.165" (4.20mm)	Insulation Height	0.165" (4.20mm)
Contact Length - Post 0.125" (3.18mm)	Contact Length - Post	0.125" (3.18mm)
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin-Lead
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?



DISCOVER

If you have any question about 801-93-020-10-002000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com