

### **8074670000 Information**



For Reference Only

Part Number8074670000ManufacturerWeidmullerCategoryRelays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 4PDT 6A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 8074670000 Specifications

Manufacturer Part Number         8074670000           Manufacturer         Weidmuller           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         RCM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         15.6mA           Coil Voltage         48VDC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         6A           Switching Voltage         240VAC - Max           Turn On Voltage (Max)         36 VDC           Turn Off Voltage (Min)         4.8 VDC           Operate Time         15ms           Release Time         10ms           Features         Test Button           Mounting Type         Socketable           Termination Style         Plug In, Quick Connect - 0.110" (2.8mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRCMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15.6mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage240VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm)	Manufacturer Part Number	8074670000
Package - Series RCM Relay Type General Purpose Coil Type Non Latching Coil Current 15.6mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 240VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Manufacturer	Weidmuller
Package-SeriesRCMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15.6mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage240VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm)	Category	Relays
SeriesRCMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15.6mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage240VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm)		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15.6mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage240VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm)	Package	-
Coil TypeNon LatchingCoil Current15.6mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage240VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time10msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm)	Series	RCM
Coil Current Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 240VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style 15.6mA 15.6mA 16.8VDC 16.8VDC 16.8VDC 17 Turn Off Voltage (Min) 18 Socketable 19 Termination Style 19 Turn Off Voltage (Min) 10 Socketable 10 Socketable 11 Turn Off Voltage (Min) 15 Socketable 16 Turn Off Voltage (Min) 17 Turn Off Voltage (Min) 18 Socketable 19 Turn Off Voltage (Min) 19 Socketable 10 Socketable 10 Socketable 10 Socketable 11 Turn Off Voltage (Min) 11 Survey (Min) 12 Survey (Min) 13 Survey (Min) 14 Survey (Min) 15 Survey (Min) 16 Survey (Min) 16 Survey (Min) 17 Survey (Min) 18 Survey (Min) 18 Survey (Min) 19 Survey (Min) 19 Survey (Min) 19 Survey (Min) 10 Surv	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 240VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 6A  Switching Voltage 240VAC - Max  Turn On Voltage (Max) 36 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 15ms  Release Time 10ms  Features Test Button  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Coil Current	15.6mA
Contact Rating (Current)  Switching Voltage  240VAC - Max  Turn On Voltage (Max)  36 VDC  Turn Off Voltage (Min)  4.8 VDC  Operate Time  15ms  Release Time  10ms  Features  Test Button  Mounting Type  Socketable  Termination Style  Plug In, Quick Connect - 0.110" (2.8mm)	Coil Voltage	48VDC
Switching Voltage 240VAC - Max  Turn On Voltage (Max) 36 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 15ms  Release Time 10ms  Features Test Button  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  4.8 VDC  Operate Time  15ms  Release Time  10ms  Features  Test Button  Mounting Type  Socketable  Termination Style  Plug In, Quick Connect - 0.110" (2.8mm)	Contact Rating (Current)	6A
Turn Off Voltage (Min)  Operate Time  15ms  Release Time  10ms  Features  Test Button  Mounting Type  Socketable  Termination Style  Plug In, Quick Connect - 0.110" (2.8mm)	Switching Voltage	240VAC - Max
Operate Time 15ms Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Turn On Voltage (Max)	36 VDC
Release Time 10ms Features Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Turn Off Voltage (Min)	4.8 VDC
Features Test Button  Mounting Type Socketable  Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Release Time	10ms
Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Features	Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, Quick Connect - 0.110" (2.8mm)
		Report errors?

#### **8074670000 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 8074670000 Payment Methods



















## 8074670000 Shipping Methods













If you have any question about 8074670000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com