

80E2C38.0 Information

Heisener.com

Part Number 80E2C38.0

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 80A 38KVAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









80E2C38.0	Specification	S
-----------	---------------	---

Manufacturer Part Number 80E2C38.0 Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 38000V (38kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)			
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating80AVoltage Rating - AC38000V (38kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	Manufacturer Part Number	80E2C38.0	
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating80AVoltage Rating - AC38000V (38kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	Manufacturer	Littelfuse Inc.	
PackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating80AVoltage Rating - AC38000V (38kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	Category	Circuit Protection	
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating80AVoltage Rating - AC38000V (38kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)		Electrical, Specialty Fuses	
Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 38000V (38kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	Package	Cartridge, Non-Standard	
Current Rating 80A Voltage Rating - AC 38000V (38kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	Series	POWR-GARD?	
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 388000V (38kV)	Fuse Type	Cartridge	
Voltage Rating - DC Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Size / Dimension - Capacity	Current Rating	80A	
Response Time	Voltage Rating - AC	38000V (38kV)	
Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	Voltage Rating - DC	-	
Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	Response Time	-	
Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	Applications	Transformer Protection	
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Size / Dimension	Features	Indicating	
Operating Temperature Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	Class	E	
Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	Approvals	-	
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	Operating Temperature	-	
Package / Case Cartridge, Non-Standard Size / Dimension 30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	Breaking Capacity @ Rated Voltage	20kA	
Size / Dimension 30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	Mounting Type	Holder	
·	Package / Case	Cartridge, Non-Standard	
Report errors?	Size / Dimension	30.875" L x 3.000" W x 6.380" H (784.23mm x 76.20mm x 162.05mm)	
		Report errors?	

80E2C38.0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

80E2C38.0 Payment Methods



















80E2C38.0 Shipping Methods













If you have any question about 80E2C38.0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com