

### 81-194632-64S Information

Heisener.com

**Part Number** 81-194632-64S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG W/SOCKETS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **81-194632-64S Specifications**

Manufacturer Part Number         81-194632-64S           Manufacturer         Amphenol Industrial Operations           Category         Connectors, Interconnects           Package         -           Series         MIL-DTL-22992, QWLD           Connector Type         Plug, Female Sockets           Number of Positions         54           Shell Size - Insert         32-64           Shell Size, MIL         -           Mounting Type         Free Hanging (In-Line)           Termination         Crimp           Fastening Type         Threaded           Orientation         N (Normal)           Ingress Protection         Waterproof           Shell Material, Finish         Aluminum, Anodic Coating (Alumilite)           Contact Finish         Gold           Features         -           Voltage - Rated         200VAC, 250VDC           Current Rating         -           Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 54 Shell Size - Insert 32-64 Shell Size, MIL  Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Manufacturer Part Number	81-194632-64S
Package-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions54Shell Size - Insert32-64Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions54Shell Size - Insert32-64Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions54Shell Size - Insert32-64Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions54Shell Size - Insert32-64Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Package	-
Number of Positions54Shell Size - Insert32-64Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Series	MIL-DTL-22992, QWLD
Shell Size - Insert Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Features - Voltage - Rated Current Rating -  32-64  32-64  32-64  Aluminum (In-Line)  Crimp  Aluminum Anodic Coating Alumilite)  Coating Coa	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Threaded Orientation N (Normal)  Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Gold  Features - Voltage - Rated 200VAC, 250VDC  Current Rating -	Number of Positions	54
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Shell Size - Insert	32-64
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Termination	Crimp
Ingress Protection  Shell Material, Finish  Contact Finish  Gold  Features  -  Voltage - Rated  Current Rating  Waterproof  Aluminum, Anodic Coating (Alumilite)  Gold  -  200VAC, 250VDC  -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating - Aluminum, Anodic Coating (Alumilite)  Gold	Orientation	N (Normal)
Contact Finish Gold  Features -  Voltage - Rated 200VAC, 250VDC  Current Rating -	Ingress Protection	Waterproof
Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 200VAC, 250VDC  Current Rating -	Contact Finish	Gold
Current Rating -	Features	-
	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	-
		Report errors?

#### 81-194632-64S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **81-194632-64S Payment Methods**



















# **81-194632-64S Shipping Methods**













If you have any question about 81-194632-64S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com