

81-194932-64S Information

Heisener.com

Part Number 81-194932-64S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG W/SOCKETS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









81-194932-64S Specifications

Manufacturer Part Number 81-194932-64S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-22992, QWLD Connector Type Receptacle, Female Sockets Number of Positions 54 Shell Size - Insert 32-64 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 200VAC, 250VDC Current Rating - Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-22992, QWLD Connector Type Receptacle, Female Sockets Number of Positions 54 Shell Size - Insert 32-64 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated Current Rating	Manufacturer Part Number	81-194932-64S
Package-SeriesMIL-DTL-22992, QWLDConnector TypeReceptacle, Female SocketsNumber of Positions54Shell Size - Insert32-64Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-22992, QWLD Connector Type Receptacle, Female Sockets Number of Positions 54 Shell Size - Insert 32-64 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 200VAC, 250VDC Current Rating	Category	Connectors, Interconnects
Series MIL-DTL-22992, QWLD Connector Type Receptacle, Female Sockets Number of Positions 54 Shell Size - Insert 32-64 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions54Shell Size - Insert32-64Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Package	-
Number of Positions54Shell Size - Insert32-64Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Series	MIL-DTL-22992, QWLD
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated Current Rating - Shell Mount, Bulkhead - Front Side Nut Crimp Gold Crimp Chimp Contact Finish Aluminum, Anodic Coating Coati	Number of Positions	54
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Size - Insert	32-64
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Termination	Crimp
Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Anodic Coating (Alumilite) Gold - Contact Finish Contact Finish Gold - - Contact Finish - - Contact Finish - Contact Finish - Contact Finish Gold - Contact Finish Contact Finish Contact Finish Contact Finish - Contact Finish Contact Finish Contact Finish Contact Finish - Contact Finish Contact Finish Contact Finish Contact Finish - Contact Finish Cont	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Ingress Protection	Waterproof
Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 200VAC, 250VDC Current Rating -	Contact Finish	Gold
Current Rating -	Features	-
	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	-
		Report errors?

81-194932-64S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

81-194932-64S Payment Methods





















81-194932-64S Shipping Methods













If you have any question about 81-194932-64S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com