



### 810F10K Information



For Reference Only

Part Number 810F10K
Manufacturer Ohmite
Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 10K OHM 1% 10W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









Manufacturer Part Number       810F10K         Manufacturer       Ohmite         Category       Resistors         Chassis Mount Resistors         Package       Axial, Box         Series       Metal-Mite?89         Resistance       10 kOhms         Tolerance       ±1%         Power (Watts)       10W         Composition       Wirewound         Temperature Coefficient       ±20ppm/°C         Operating Temperature       -55°C ~ 275°C         Features       -         Coating, Housing Type       Aluminum         Mounting Feature       Flanges         Size / Dimension       0.750" L x 0.812" W (19.05mm x 20.63mm)         Height - Seated (Max)       0.400" (10.16mm)		
Category         Resistors           Chassis Mount Resistors           Package         Axial, Box           Series         Metal-Mite?89           Resistance         10 kOhms           Tolerance         ±1%           Power (Watts)         10W           Composition         Wirewound           Temperature Coefficient         ±20ppm/°C           Operating Temperature         -55°C ~ 275°C           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         0.750" L x 0.812" W (19.05mm x 20.63mm)           Height - Seated (Max)         0.400" (10.16mm)	Manufacturer Part Number	810F10K
Chassis Mount Resistors           Package         Axial, Box           Series         Metal-Mite?89           Resistance         10 kOhms           Tolerance         ±1%           Power (Watts)         10W           Composition         Wirewound           Temperature Coefficient         ±20ppm/°C           Operating Temperature         -55°C ~ 275°C           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         0.750" L x 0.812" W (19.05mm x 20.63mm)           Height - Seated (Max)         0.400" (10.16mm)	Manufacturer	Ohmite
PackageAxial, BoxSeriesMetal-Mite?89Resistance10 kOhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.812" W (19.05mm x 20.63mm)Height - Seated (Max)0.400" (10.16mm)	Category	Resistors
Series         Metal-Mite?89           Resistance         10 kOhms           Tolerance         ±1%           Power (Watts)         10W           Composition         Wirewound           Temperature Coefficient         ±20ppm/°C           Operating Temperature         -55°C ~ 275°C           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         0.750" L x 0.812" W (19.05mm x 20.63mm)           Height - Seated (Max)         0.400" (10.16mm)		Chassis Mount Resistors
Resistance 10 kOhms  Tolerance $\pm 1\%$ Power (Watts) 10W  Composition Wirewound  Temperature Coefficient $\pm 20$ ppm/°C  Operating Temperature $-55^{\circ}$ C $\sim 275^{\circ}$ C  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.750" L x 0.812" W (19.05mm x 20.63mm)  Height - Seated (Max) 0.400" (10.16mm)	Package	Axial, Box
Tolerance $\pm 1\%$ Power (Watts) $10W$ CompositionWirewoundTemperature Coefficient $\pm 20\text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 275^{\circ}\text{C}$ Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $0.750^{\circ}\text{L x } 0.812^{\circ}\text{W } (19.05\text{mm x } 20.63\text{mm})$ Height - Seated (Max) $0.400^{\circ}$ (10.16mm)	Series	Metal-Mite?89
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±20ppm/°C  Operating Temperature  -55°C ~ 275°C  Features  -  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.750" L x 0.812" W (19.05mm x 20.63mm)  Height - Seated (Max)  0.400" (10.16mm)	Resistance	10 kOhms
CompositionWirewoundTemperature Coefficient $\pm 20 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 275^{\circ}\text{C}$ Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $0.750^{\circ}\text{L x } 0.812^{\circ}\text{W } (19.05 \text{mm x } 20.63 \text{mm})$ Height - Seated (Max) $0.400^{\circ}$ (10.16 mm)	Tolerance	$\pm 1\%$
Temperature Coefficient $\pm 20$ ppm/°C  Operating Temperature $-55$ °C $\sim 275$ °C  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.750" L x 0.812" W (19.05mm x 20.63mm)  Height - Seated (Max) 0.400" (10.16mm)	Power (Watts)	10W
Operating Temperature $-55^{\circ}\text{C} \sim 275^{\circ}\text{C}$ Features - Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 0.750" L x 0.812" W (19.05mm x 20.63mm)  Height - Seated (Max) 0.400" (10.16mm)	Composition	Wirewound
Features - Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 0.750" L x 0.812" W (19.05mm x 20.63mm) Height - Seated (Max) 0.400" (10.16mm)	Temperature Coefficient	±20ppm/°C
Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 0.750" L x 0.812" W (19.05mm x 20.63mm)  Height - Seated (Max) 0.400" (10.16mm)	Operating Temperature	-55°C ~ 275°C
Mounting Feature Flanges Size / Dimension 0.750" L x 0.812" W (19.05mm x 20.63mm) Height - Seated (Max) 0.400" (10.16mm)	Features	-
Size / Dimension         0.750" L x 0.812" W (19.05mm x 20.63mm)           Height - Seated (Max)         0.400" (10.16mm)	Coating, Housing Type	Aluminum
Height - Seated (Max) 0.400" (10.16mm)	Mounting Feature	Flanges
-	Size / Dimension	0.750" L x 0.812" W (19.05mm x 20.63mm)
	Height - Seated (Max)	0.400" (10.16mm)
Lead Style Solder Lugs	Lead Style	Solder Lugs
Package / Case Axial, Box	Package / Case	Axial, Box
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

### 810F10K Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 810F10K Payment Methods



















# 810F10K Shipping Methods













If you have any question about 810F10K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com