

810F3K0 Information



For Reference Only

Part Number810F3K0ManufacturerOhmiteCategoryResistors

Chassis Mount Resistors

Description RES CHAS MNT 3K OHM 1% 10W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









810F3K0 Specifications

Manufacturer Part Number810F3K0ManufacturerOhmiteCategoryResistorsChassis Mount ResistorsPackageAxial, BoxSeriesMetal-Mite?89Resistance3 kOhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlanges
CategoryResistorsChassis Mount ResistorsPackageAxial, BoxSeriesMetal-Mite?89Resistance3 kOhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlanges
Chassis Mount Resistors Package Axial, Box Series Metal-Mite?89 Resistance 3 kOhms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges
PackageAxial, BoxSeriesMetal-Mite?89Resistance3 kOhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlanges
SeriesMetal-Mite?89Resistance3 kOhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeatures-Coating, Housing TypeAluminumMounting FeatureFlanges
Resistance 3 kOhms Tolerance $\pm 1\%$ Power (Watts) $10W$ CompositionWirewoundTemperature Coefficient $\pm 20 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 275^{\circ}\text{C}$ Features-Coating, Housing TypeAluminumMounting FeatureFlanges
Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges
Power (Watts) $10W$ CompositionWirewoundTemperature Coefficient $\pm 20 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 275^{\circ}\text{C}$ Features-Coating, Housing TypeAluminumMounting FeatureFlanges
CompositionWirewoundTemperature Coefficient $\pm 20 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 275^{\circ}\text{C}$ Features-Coating, Housing TypeAluminumMounting FeatureFlanges
Temperature Coefficient $\pm 20 \mathrm{ppm/^{\circ}C}$ Operating Temperature $-55^{\circ}\mathrm{C} \sim 275^{\circ}\mathrm{C}$ Features-Coating, Housing TypeAluminumMounting FeatureFlanges
Operating Temperature -55°C ~ 275°C Features - Coating, Housing Type Aluminum Mounting Feature Flanges
Features - Coating, Housing Type Aluminum Mounting Feature Flanges
Coating, Housing Type Aluminum Mounting Feature Flanges
Mounting Feature Flanges
Size / Dimension 0.750" L x 0.812" W (19.05mm x 20.63mm)
Height - Seated (Max) 0.400" (10.16mm)
Lead Style Solder Lugs
Package / Case Axial, Box
Failure Rate -
Report errors?

810F3K0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

810F3K0 Payment Methods





















810F3K0 Shipping Methods













If you have any question about 810F3K0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com