



822B026-273L801 Information

Heisener.com

Part Number 822B026-273L801 Manufacturer NorComp Inc.

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT FMALE 26POS GOLD SLDR

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









822B026-273L801 Specifications

Manufacturer Part Number 822B026-273L801 Manufacturer NorComp Inc. Category Connectors, Interconnects Package - Series QUIK-LOQ? 822B Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Nickel Plated Contact Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated 315V Current Rating - Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series QUIK-LOQ? 822B Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Farmination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection Shell Material, Finish Brass, Nickel Plated Contact Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated Current Rating -	Manufacturer Part Number	822B026-273L801
Package-SeriesQUIK-LOQ? 822BConnector TypeReceptacle, Female SocketsNumber of Positions26Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Nickel PlatedContact FinishGoldFeaturesBackshell, Shielded, Strain ReliefVoltage - Rated315VCurrent Rating-	Manufacturer	NorComp Inc.
Package - QUIK-LOQ? 822B Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated 315V Current Rating -	Category	Connectors, Interconnects
Series QUIK-LOQ? 822B Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Nickel Plated Contact Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated 315V Current Rating -		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions26Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishBrass, Nickel PlatedContact FinishGoldFeaturesBackshell, Shielded, Strain ReliefVoltage - Rated315VCurrent Rating-	Package	-
Number of Positions Shell Size - Insert - Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Nickel Plated Contact Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated Current Rating -	Series	QUIK-LOQ? 822B
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Nickel Plated Contact Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Nickel Plated Contact Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated Current Rating -	Number of Positions	26
Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Nickel Plated Contact Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated 315V Current Rating -	Shell Size - Insert	-
Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Nickel Plated Contact Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated 315V Current Rating -	Shell Size, MIL	-
Fastening Type Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Nickel Plated Contact Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Nickel Plated Contact Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated 315V Current Rating -	Termination	Solder Cup
Ingress Protection IP50 - Dust Protected Shell Material, Finish Brass, Nickel Plated Contact Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated Current Rating -	Fastening Type	Push-Pull
Shell Material, Finish Contact Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated Current Rating	Orientation	Keyed
Contact Finish Gold Features Backshell, Shielded, Strain Relief Voltage - Rated 315V Current Rating -	Ingress Protection	IP50 - Dust Protected
Features Backshell, Shielded, Strain Relief Voltage - Rated 315V Current Rating -	Shell Material, Finish	Brass, Nickel Plated
Voltage - Rated 315V Current Rating -	Contact Finish	Gold
Current Rating -	Features	Backshell, Shielded, Strain Relief
	Voltage - Rated	315V
Report errors?	Current Rating	-
		Report errors?

822B026-273L801 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

822B026-273L801 Payment Methods



















822B026-273L801 Shipping Methods













If you have any question about 822B026-273L801, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com