

825A4620G Information

Heisener.com

Part Number 825A4620G Manufacturer Tamura

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 9V 11W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









825A4620G Specifications

| Manufacturer Part Number Manufacturer Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package Series Region Utilized North America Desktop (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output Voltage - Output (Max) Power (Watts) Negative Center Applications ITE (Commercial) Efficiency Operating Temperature Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters - Series - Region Utilized North America Desktop (Class I) Input Type Fixed Blade 120VAC 120VAC 9V Current - Output (Max) 1.2A Power (Watts) ITE (Commercial) Efficiency - Operating Temperature | • | |
|--|---------------------------|--|
| Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized North America Form Desktop (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1.2A Power (Watts) 11W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - | Manufacturer Part Number | 825A4620G |
| AC DC Desktop, Wall Adapters Package Series - Region Utilized North America Form Desktop (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) Power (Watts) 11W No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency - | Manufacturer | Tamura |
| Package Series - Region Utilized North America Form Desktop (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) Power (Watts) 11W No Load Power Consumption Polarization Negative Center Applications ITE (Commercial) Efficiency - | Category | Power Supplies - External/Internal (Off-Board) |
| Series - Region Utilized North America Form Desktop (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1.2A Power (Watts) 11W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - | | AC DC Desktop, Wall Adapters |
| Region Utilized North America Form Desktop (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1.2A Power (Watts) 11W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - | Package | - |
| Form Desktop (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1.2A Power (Watts) 11W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - | Series | - |
| Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 1.2A Power (Watts) 11W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - | Region Utilized | North America |
| Voltage - Input Voltage - Output 9V Current - Output (Max) 1.2A Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency 120VAC 120VAC 9V 1.2A 1.2A 1.2A 1.2B 1.2C 1.2 | Form | Desktop (Class I) |
| Voltage - Output 9V Current - Output (Max) 1.2A Power (Watts) 11W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - | Input Type | Fixed Blade |
| Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency - | Voltage - Input | 120VAC |
| Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency - | Voltage - Output | 9V |
| No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency - | Current - Output (Max) | 1.2A |
| Polarization Negative Center Applications ITE (Commercial) Efficiency - | Power (Watts) | 11W |
| Applications ITE (Commercial) Efficiency - | No Load Power Consumption | - |
| Efficiency - | Polarization | Negative Center |
| | Applications | ITE (Commercial) |
| Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ | Efficiency | - |
| | Operating Temperature | 0°C ~ 40°C |
| Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm | Output Connector | Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm |
| Size / Dimension 3.27" L x 2.41" W x 2.21" H (83.0mm x 61.0mm x 56.0mm) | Size / Dimension | 3.27" L x 2.41" W x 2.21" H (83.0mm x 61.0mm x 56.0mm) |
| Report errors | | Report errors? |

825A4620G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

825A4620G Payment Methods



















825A4620G Shipping Methods













If you have any question about 825A4620G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com