

8286280000 Information

Mai Cate

Part Number8286280000ManufacturerWeidmullerCategoryRelays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 5A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









8286280000 Specifications
ozoozoooo speemeutions

Manufacturer Part Number 8286280000 Manufacturer Weidmuller Category Relays Power Relays, Over 2 Amps Package - Series - Relay Type General Purpose with Socket Coil Type Non Latching Coil Current - Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 5ms Release Time 4ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	•	
CategoryRelaysPackage-Series-Relay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current-Coil Voltage48VAC/DCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time5msRelease Time4msFeatures-Mounting TypeDIN Rail	Manufacturer Part Number	8286280000
Package-Series-Relay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current-Coil Voltage48VAC/DCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time5msRelease Time4msFeatures-Mounting TypeDIN Rail	Manufacturer	Weidmuller
Package-Series-Relay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current-Coil Voltage48VAC/DCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time5msRelease Time4msFeatures-Mounting TypeDIN Rail	Category	Relays
Series - General Purpose with Socket Coil Type Non Latching Coil Current - Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 5ms Release Time 4ms Features - Mounting Type DIN Rail		Power Relays, Over 2 Amps
Relay Type General Purpose with Socket Coil Type Non Latching Coil Current - Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 5ms Release Time 4ms Features - Mounting Type DIN Rail	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage48VAC/DCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time5msRelease Time4msFeatures-Mounting TypeDIN Rail	Series	-
Coil Current - Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 5ms Release Time 4ms Features - Mounting Type DIN Rail	Relay Type	General Purpose with Socket
Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 5ms Release Time 4ms Features - Mounting Type DIN Rail	Coil Type	Non Latching
Contact Form C) Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time 4ms Features Mounting Type SPDT (1 Form C) 5A 250VAC - Max - 4ms DIN Rail	Coil Current	-
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 5ms Release Time 4ms Features - Mounting Type DIN Rail	Coil Voltage	48VAC/DC
Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time 4ms Features Mounting Type DIN Rail	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time 4ms Features - Mounting Type DIN Rail	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time Sms Release Time 4ms Features - Mounting Type DIN Rail	Switching Voltage	250VAC - Max
Operate Time5msRelease Time4msFeatures-Mounting TypeDIN Rail	Turn On Voltage (Max)	-
Release Time 4ms Features - Mounting Type DIN Rail	Turn Off Voltage (Min)	-
Features - Mounting Type DIN Rail	Operate Time	5ms
Mounting Type DIN Rail	Release Time	4ms
	Features	-
Termination Style Screw Terminal	Mounting Type	DIN Rail
· · · · · · · · · · · · · · · · · · ·	Termination Style	Screw Terminal
Report errors?		Report errors?

8286280000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

8286280000 Payment Methods





















8286280000 Shipping Methods













If you have any question about 8286280000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com