

830A0061-03 Information

Heisener.com

Part Number 830A0061-03 Manufacturer Tamura

> Category Power Supplies - External/Internal (Off-Board)

AC AC Wall Adapters

Description AC/AC WALL MOUNT ADAPTER 12V 19W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









830A0061-03 Specifications

Manufacturer Part Number830A0061-03ManufacturerTamuraCategoryPower Supplies - External/Internal (Off-Board)AC AC Wall AdaptersPackage-Series830ARegion UtilizedNorth AmericaFormWall Mount (Class I)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)1.6APower (Watts)19WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorScrew TerminalSize / Dimension-Approvals-		
CategoryPower Supplies - External/Internal (Off-Board)AC AC Wall AdaptersPackage-Series830ARegion UtilizedNorth AmericaFormWall Mount (Class I)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)1.6APower (Watts)19WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorScrew TerminalSize / Dimension-	Manufacturer Part Number	830A0061-03
Package - Series 830A Region Utilized North America Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal Size / Dimension -	Manufacturer	Tamura
Package - Series 830A Region Utilized North America Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 120VAC Current - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Output Connector Screw Terminal Size / Dimension - Series Insurance Screw Terminal Size / Dimension - Series Insurance Screw Terminal	Category	Power Supplies - External/Internal (Off-Board)
Series830ARegion UtilizedNorth AmericaFormWall Mount (Class I)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)1.6APower (Watts)19WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorScrew TerminalSize / Dimension-		AC AC Wall Adapters
Region UtilizedNorth AmericaFormWall Mount (Class I)Input TypeFixed BladeVoltage - Input120VACVoltage - Output12VACCurrent - Output (Max)1.6APower (Watts)19WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorScrew TerminalSize / Dimension-	Package	-
Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal Size / Dimension -	Series	830A
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal Size / Dimension -	Region Utilized	North America
Voltage - Input 120VAC Voltage - Output 12VAC Current - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption - Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Size / Dimension 120VAC 12VAC 12VAC 12VAC 1.6A 1.6A 19W - Commercial	Form	Wall Mount (Class I)
Voltage - Output (Max) 1.6A Power (Watts) 19W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal Size / Dimension -	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Screw Terminal Size / Dimension 1.6A 1.6A 1.6W 1	Voltage - Input	120VAC
Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Size / Dimension 19W	Voltage - Output	12VAC
No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal Size / Dimension -	Current - Output (Max)	1.6A
Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal Size / Dimension -	Power (Watts)	19W
Efficiency - Operating Temperature - Output Connector Screw Terminal Size / Dimension -	No Load Power Consumption	-
Operating Temperature - Output Connector Screw Terminal Size / Dimension -	Applications	ITE (Commercial)
Output Connector Screw Terminal Size / Dimension -	Efficiency	-
Size / Dimension -	Operating Temperature	-
	Output Connector	Screw Terminal
Approvals -	Size / Dimension	-
	Approvals	-
Report errors?		Report errors?

830A0061-03 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

830A0061-03 Payment Methods



















830A0061-03 Shipping Methods













If you have any question about 830A0061-03, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com