

830A0062-03 Information

Heisener.com

Part Number 830A0062-03 Manufacturer Tamura

Category Power Supplies - External/Internal (Off-Board)

AC AC Wall Adapters

Description AC/AC WALL MOUNT ADAPTER 14V 20W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









830A0062-03 Specifications

Manufacturer Part Number 830A0062-03 Manufacturer Tamura Category Power Supplies - External/Internal (Off-Board) AC AC Wall Adapters Package - Series 830A Region Utilized North America Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 14VAC Current - Output (Max) 1.43A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal		
Category Power Supplies - External/Internal (Off-Board) AC AC Wall Adapters Package - Series 830A Region Utilized North America Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 14VAC Current - Output (Max) 1.43A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency Operating Temperature -	Manufacturer Part Number	830A0062-03
Package - Series 830A Region Utilized North America Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 14VAC Current - Output (Max) 1.43A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature -	Manufacturer	Tamura
Package - 830A Region Utilized North America Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 14VAC Current - Output (Max) 1.43A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency Operating Temperature	Category	Power Supplies - External/Internal (Off-Board)
Series830ARegion UtilizedNorth AmericaFormWall Mount (Class I)Input TypeFixed BladeVoltage - Input120VACVoltage - Output14VACCurrent - Output (Max)1.43APower (Watts)20WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-		AC AC Wall Adapters
Region Utilized North America Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 14VAC Current - Output (Max) 1.43A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature -	Package	-
Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 14VAC Current - Output (Max) 1.43A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature -	Series	830A
Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 14VAC Current - Output (Max) 1.43A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature -	Region Utilized	North America
Voltage - Input Voltage - Output 14VAC Current - Output (Max) Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature 120VAC 14VAC 20W ITE (Commercial)	Form	Wall Mount (Class I)
Voltage - Output (Max) 1.43A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature -	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature 1.43A 20W	Voltage - Input	120VAC
Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature	Voltage - Output	14VAC
No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature -	Current - Output (Max)	1.43A
Applications ITE (Commercial) Efficiency - Operating Temperature -	Power (Watts)	20W
Efficiency - Operating Temperature -	No Load Power Consumption	-
Operating Temperature -	Applications	ITE (Commercial)
	Efficiency	-
Output Connector Screw Terminal	Operating Temperature	-
output connector below reminiar	Output Connector	Screw Terminal
Size / Dimension -	Size / Dimension	-
Approvals -	Approvals	-
Report errors?		Report errors?

830A0062-03 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

830A0062-03 Payment Methods


































If you have any question about 830A0062-03, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com