

830A0063-03 Information

Heisener.com

Part Number 830A0063-03 Manufacturer Tamura

Category Power Supplies - External/Internal (Off-Board)

AC AC Wall Adapters

Description AC/AC WALL MOUNT ADAPTER 16V 20W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









830A0063-03 Specifications

| Manufacturer Part Number 830A0063-03 Manufacturer Tamura Category Power Supplies - External/Internal (Off-Board) AC AC Wall Adapters AC AC Wall Adapters Package - Series 830A Region Utilized North America Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 16VAC Current - Output (Max) 1.25A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal Size / Dimension - | | |
|--|---------------------------|--|
| Category Power Supplies - External/Internal (Off-Board) AC AC Wall Adapters Package - Series 830A Region Utilized North America Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 16VAC Current - Output (Max) 1.25A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal | Manufacturer Part Number | 830A0063-03 |
| Package - Series 830A Region Utilized North America Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 16VAC Current - Output (Max) 1.25A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal | Manufacturer | Tamura |
| Package - Series 830A Region Utilized North America Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 16VAC Current - Output (Max) 1.25A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Output Temperature - Output Connector Screw Terminal | Category | Power Supplies - External/Internal (Off-Board) |
| Series830ARegion UtilizedNorth AmericaFormWall Mount (Class I)Input TypeFixed BladeVoltage - Input120VACVoltage - Output16VACCurrent - Output (Max)1.25APower (Watts)20WNo Load Power Consumption-ApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorScrew Terminal | | AC AC Wall Adapters |
| Region Utilized North America Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 16VAC Current - Output (Max) 1.25A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal | Package | - |
| Form Wall Mount (Class I) Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 16VAC Current - Output (Max) 1.25A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal | Series | 830A |
| Input Type Voltage - Input 120VAC Voltage - Output 16VAC Current - Output (Max) 1.25A Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Fixed Blade Fixed Blade 120VAC 16VAC 1.25A 20W TIE (Commercial) Fixed Blade 16VAC 1.25A 1.25A 20W Sow Temperature - Operating Temperature Screw Terminal | Region Utilized | North America |
| Voltage - Input 120VAC Voltage - Output 16VAC Current - Output (Max) 1.25A Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector 120VAC 16VAC 1.25A 20W T.25A Power (Watts) - Commercial) Screw Terminal | Form | Wall Mount (Class I) |
| Voltage - Output (Max) 1.25A Power (Watts) 20W No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal | Input Type | Fixed Blade |
| Current - Output (Max) Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector 1.25A 1.25A 1.25A For a commercial commercia | Voltage - Input | 120VAC |
| Power (Watts) No Load Power Consumption Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Screw Terminal | Voltage - Output | 16VAC |
| No Load Power Consumption - Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal | Current - Output (Max) | 1.25A |
| Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Screw Terminal | Power (Watts) | 20W |
| Efficiency - Operating Temperature - Output Connector Screw Terminal | No Load Power Consumption | - |
| Operating Temperature - Output Connector Screw Terminal | Applications | ITE (Commercial) |
| Output Connector Screw Terminal | Efficiency | - |
| 1 | Operating Temperature | - |
| Size / Dimension - | Output Connector | Screw Terminal |
| | Size / Dimension | - |
| Approvals - | Approvals | - |
| Report errors? | | Report errors? |

830A0063-03 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

830A0063-03 Payment Methods





















830A0063-03 Shipping Methods













If you have any question about 830A0063-03, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com