

#### 833-87-024-10-001101 Information



For Reference Only

**Part Number** 833-87-024-10-001101

Manufacturer Preci-Dip

**Category** Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** PCB CONN SOLDER TAIL 2MM

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 833-87-024-10-001101 Specifications

Manufacturer Part Number833-87-024-10-001101ManufacturerPreci-DipCategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series833Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlash		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets  Package - Series 833 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Manufacturer Part Number	833-87-024-10-001101
Rectangular Connectors - Headers, Receptacles, Female Sockets  Package Series 833 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Manufacturer	Preci-Dip
Package - Series 833  Connector Type Socket  Contact Type Female Socket  Style Board to Board  Number of Positions 24  Number of Positions Loaded All  Pitch - Mating 0.079" (2.00mm)  Number of Rows 2  Row Spacing - Mating 0.079" (2.00mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating Flash	Category	Connectors, Interconnects
Series 833 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type  Contact Type  Female Socket  Style  Board to Board  Number of Positions  24  Number of Positions Loaded  All  Pitch - Mating  0.079" (2.00mm)  Number of Rows  2  Row Spacing - Mating  0.079" (2.00mm)  Mounting Type  Through Hole  Termination  Solder  Fastening Type  Push-Pull  Contact Finish - Mating  Gold  Contact Finish Thickness - Mating  Flash	Package	-
Contact Type Female Socket  Style Board to Board  Number of Positions 24  Number of Positions Loaded All  Pitch - Mating 0.079" (2.00mm)  Number of Rows 2  Row Spacing - Mating 0.079" (2.00mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating Flash	Series	833
Style Board to Board  Number of Positions 24  Number of Positions Loaded All  Pitch - Mating 0.079" (2.00mm)  Number of Rows 2  Row Spacing - Mating 0.079" (2.00mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating Flash	Connector Type	Socket
Number of Positions 24  Number of Positions Loaded All  Pitch - Mating 0.079" (2.00mm)  Number of Rows 2  Row Spacing - Mating 0.079" (2.00mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating Flash	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlash	Style	Board to Board
Pitch - Mating 0.079" (2.00mm)  Number of Rows 2  Row Spacing - Mating 0.079" (2.00mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating Flash	Number of Positions	24
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlash	Number of Positions Loaded	All
Row Spacing - Mating 0.079" (2.00mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating Flash	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlash	Number of Rows	2
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Row Spacing - Mating	0.079" (2.00mm)
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Mounting Type	Through Hole
Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash	Termination	Solder
Contact Finish Thickness - Mating Flash	Fastening Type	Push-Pull
•	Contact Finish - Mating	Gold
	Contact Finish Thickness - Mating	Flash
Insulation Color Black	Insulation Color	Black
Insulation Height 0.165" (4.20mm)	Insulation Height	0.165" (4.20mm)
Contact Length - Post 0.125" (3.18mm)	Contact Length - Post	0.125" (3.18mm)
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

#### 833-87-024-10-001101 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 833-87-024-10-001101 Payment Methods



















### 833-87-024-10-001101 Shipping Methods













If you have any question about 833-87-024-10-001101, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com