

8418310000 Information

Manufacture Category

Part Number 8418310000 Manufacturer Weidmuller Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









8418310000 Specifications

Manufacturer Part Number8418310000ManufacturerWeidmullerCategoryRelaysPackage-Series-Relay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current15mACoil Voltage48VAC/DCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time7msRelease Time5msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal		
CategoryRelaysPackage-Series-Relay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current15mACoil Voltage48VAC/DCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time7msRelease Time5msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal	Manufacturer Part Number	8418310000
Package - Series - General Purpose with Socket Coil Type General Purpose with Socket 15mA 15mA 15mA 15mA 15mA 15mA 15mA 15mA	Manufacturer	Weidmuller
Package-Series-Relay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current15mACoil Voltage48VAC/DCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time7msRelease Time5msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal	Category	Relays
Series-Relay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current15mACoil Voltage48VAC/DCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time7msRelease Time5msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current15mACoil Voltage48VAC/DCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time7msRelease Time5msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal	Package	-
Coil TypeNon LatchingCoil Current15mACoil Voltage48VAC/DCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time7msRelease Time5msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal	Series	-
Coil Current Coil Voltage 48VAC/DC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 7ms Release Time 5ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Relay Type	General Purpose with Socket
Coil Voltage 48VAC/DC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 7ms Release Time 5ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Features Mounting Type DIN Rail Termination Style	Coil Current	15mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 7ms Release Time 5ms Features - Mounting Type DIN Rail Termination Style	Coil Voltage	48VAC/DC
Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time 7ms Release Time 5ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time 5ms Features - Mounting Type DIN Rail Termination Style	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 7ms Release Time 5ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Switching Voltage	250VAC - Max
Operate Time7msRelease Time5msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal	Turn On Voltage (Max)	-
Release Time 5ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Turn Off Voltage (Min)	-
Features - Mounting Type DIN Rail Termination Style Screw Terminal	Operate Time	7ms
Mounting Type DIN Rail Termination Style Screw Terminal	Release Time	5ms
Termination Style Screw Terminal	Features	-
	Mounting Type	DIN Rail
Report errors?	Termination Style	Screw Terminal
1		Report errors?

8418310000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

8418310000 Payment Methods



















8418310000 Shipping Methods













If you have any question about 8418310000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com