

85-194640-57S Information

Heisener.com

Part Number 85-194640-57S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG W/SOCKETS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









85-194640-57S Specifications

Manufacturer Part Number85-194640-578ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert40-57Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated1250VAC, 1750VDCCurrent Rating-Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 40-57 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Manufacturer Part Number	85-194640-57S
Circular Connectors Package - Series MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 40-57 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert40-57Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated1250VAC, 1750VDCCurrent Rating-	Category	Connectors, Interconnects
Series MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 40-57 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert40-57Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishGoldFeatures-Voltage - Rated1250VAC, 1750VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 40-57 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Voltage - Rated 1250VAC, 1750VDC Current Rating -	Series	MIL-DTL-22992, QWLD
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated Current Rating - 40-57 Augustian - Free Hanging (In-Line) Free Hanging (In-Line) Augustian - Threaded Aluminum N (Normal) Ball Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Contact Finish Features - Voltage - Rated 1250VAC, 1750VDC	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features Voltage - Rated 1250VAC, 1750VDC Current Rating -	Number of Positions	4
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Shell Size - Insert	40-57
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Gold Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Termination	Crimp
Ingress Protection Shell Material, Finish Contact Finish Gold Features Voltage - Rated Current Rating Waterproof Aluminum, Anodic Coating (Alumilite) Gold	Fastening Type	Threaded
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Anodic Coating (Alumilite) Gold - - - - - - - - - - - - -	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Ingress Protection	Waterproof
Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 1250VAC, 1750VDC Current Rating -	Contact Finish	Gold
Current Rating -	Features	-
	Voltage - Rated	1250VAC, 1750VDC
Report errors?	Current Rating	-
		Report errors?

85-194640-57S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

85-194640-57S Payment Methods





















85-194640-57S Shipping Methods













If you have any question about 85-194640-57S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com