

### 85106J833S50 Information

Heisener.com

**Part Number** 85106J833S50

Manufacturer Souriau

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 3POS STRAIGHT W/SCKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 85106J833S50 Specifications

| Manufacturer Part Number85106J833S50ManufacturerSouriauCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482, 851Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert8-33Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesSealing GlandVoltage - Rated-Current Rating7.5A |                          |   |    |
|---|--------------------------|---|----|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482, 851Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert8-33Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesSealing GlandVoltage - Rated-Current Rating7.5A  | Manufacturer Part Number | 85106J833S50                                      |    |
| Package-SeriesMIL-DTL-26482, 851Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert8-33Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesSealing GlandVoltage - Rated-Current Rating7.5A   | Manufacturer             | Souriau   |    |
| Package - MIL-DTL-26482, 851 Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 8-33 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Sealing Gland Voltage - Rated Current Rating 7.5A   | Category                 | Connectors, Interconnects                         |    |
| SeriesMIL-DTL-26482, 851Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert8-33Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesSealing GlandVoltage - Rated-Current Rating7.5A   |                          | Circular Connectors                               |    |
| Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert8-33Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesSealing GlandVoltage - Rated-Current Rating7.5A   | Package                  | -   |    |
| Number of Positions3Shell Size - Insert8-33Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesSealing GlandVoltage - Rated-Current Rating7.5A   | Series                   | MIL-DTL-26482, 851                                |    |
| Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Sealing Gland Voltage - Rated - Current Rating 7.5A  | Connector Type           | Plug, Female Sockets                              |    |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Gold Features Sealing Gland  Voltage - Rated - Current Rating 7.5A   | Number of Positions      | 3   |    |
| Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesSealing GlandVoltage - Rated-Current Rating7.5A  | Shell Size - Insert      | 8-33  |    |
| Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Sealing Gland Voltage - Rated - Current Rating 7.5A   | Shell Size, MIL          | -   |    |
| Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Sealing Gland Voltage - Rated - Current Rating 7.5A   | Mounting Type            | Free Hanging (In-Line)                            |    |
| Orientation N (Normal) Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Sealing Gland Voltage - Rated - Current Rating 7.5A   | Termination              | Solder Cup  |    |
| Ingress Protection  IP65/67 - Dust Tight, Water Resistant, Waterproof  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Gold  Features  Sealing Gland  Voltage - Rated  -  Current Rating  7.5A   | Fastening Type           | Bayonet Lock                                      |    |
| Shell Material, Finish  Contact Finish  Gold  Features  Sealing Gland  Voltage - Rated  - Current Rating  7.5A  | Orientation              | N (Normal)  |    |
| Contact Finish Gold Features Sealing Gland Voltage - Rated - Current Rating 7.5A  | Ingress Protection       | IP65/67 - Dust Tight, Water Resistant, Waterproof |    |
| Features Sealing Gland  Voltage - Rated - Current Rating 7.5A   | Shell Material, Finish   | Aluminum Alloy, Olive Drab Cadmium Plated         |    |
| Voltage - Rated - Current Rating 7.5A   | Contact Finish           | Gold  |    |
| Current Rating 7.5A   | Features                 | Sealing Gland                                     |    |
| -   | Voltage - Rated          | -   |    |
| Report errors?  | Current Rating           | 7.5A  |    |
|   |                          | Report errors                                     | 3? |

#### **85106J833S50** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 85106J833S50 Payment Methods





















## 85106J833S50 Shipping Methods













If you have any question about 85106J833S50, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com