

85106JC1210S50

85106JC1210S50 Information

Heisener.com Gidal Write Land Terr	Part Number Manufacturer Category Description Package	85106JC1210S50 Souriau Connectors, Interconnects Circular Connectors CONN PLUG 10POS STRAIGHT W/SCKT - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



85106JC1210S50 Specifications

ManufacturerSouriauCategoryConnectors, InterconnectsCategoryCircular ConnectorsPackage-Package-SeriesMIL-DTL-26482, 851Connector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)FerminationSolder CupFastening TypeBayonet LockDrientationN (Normal)ngress ProtectionP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldContact FinishGoldVoltage - Rated-		
CategoryConnectors, InterconnectsCarcular ConnectorsPackage-SeriesMIL-DTL-26482, 851Connector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)FerminationSolder CupFastening TypeBayonet LockDrientationN(Normal)Ingress ProtectionP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldContact FinishGoldContact Finish-Voltage - Rated-Current Rating7.5A	Manufacturer Part Number	85106JC1210S50
Circular ConnectorsPackage-SeriesMIL-DTL-26482, 851Connector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)FerminationSolder CupPastening TypeBayonet LockOrientationN(Normal)Ingess ProtectionPfo5/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldContact FinishGoldVoltage - Rated-Current Rating7.5A	Manufacturer	Souriau
Package-SeriesMIL-DTL-26482, 851Connector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)FerminationSolder CupPastening TypeBayonet LockDrientationN(Normal)ngress ProtectionP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedGoldage - Rated-Current Rating7.5A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482, 851Connector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)ForminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldContact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)FerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldContact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A	Package	-
Number of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)Mounting TypeSolder CupFastening TypeBayonet LockPrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A	Series	MIL-DTL-26482, 851
Shell Size - Insert12-10Shell Size, MIL-Mounting TypeFree Hanging (In-Line)FerminationSolder CupFastening TypeBayonet LockDrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishGoldContact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A	Connector Type	Plug, Female Sockets
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)FerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A	Number of Positions	10
Mounting TypeFree Hanging (In-Line)FerminationSolder CupFastening TypeBayonet LockDrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Turrent Rating7.5A	Shell Size - Insert	12-10
FerminationSolder CupFastening TypeBayonet LockDrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A	Shell Size, MIL	-
Fastening TypeBayonet LockDrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A	Mounting Type	Free Hanging (In-Line)
DrientationN (Normal)ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A	Termination	Solder Cup
Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A	Fastening Type	Bayonet Lock
Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A	Orientation	N (Normal)
Contact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A	Ingress Protection	IP65/67 - Dust Tight, Water Resistant, Waterproof
FeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated - Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Cable Clamp, Sealing Gland
-	Voltage - Rated	-
Report errors?	Current Rating	7.5A
		Report errors?

85106JC1210S50 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

85106JC1210S50 Payment Methods





If you have any question about 85106JC1210S50, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com