



85106JC84P50 Information

Heisener.com

Part Number 85106JC84P50

Manufacturer Souriau

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 4POS STRAIGHT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









85106JC84P50 Specifications

| Manufacturer Part Number 85106JC84P50 Manufacturer Souriau Category Connectors, Interconnects Package - Series MIL-DTL-26482, 851 Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 8-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp, Sealing Gland Voltage - Rated - Current Rating 7.5A | | | |
|---|--------------------------|---|---|
| Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482, 851 Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 8-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Cable Clamp, Sealing Gland Voltage - Rated - Current Rating 7.5A | Manufacturer Part Number | 85106JC84P50 | |
| Package - Series MIL-DTL-26482, 851 Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 8-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp, Sealing Gland Voltage - Rated Current Rating 7,5A | Manufacturer | Souriau | |
| Package - MIL-DTL-26482, 851 Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 8-4 Shell Size, MIL - Chapter Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp, Sealing Gland Voltage - Rated Current Rating 7,5A | Category | Connectors, Interconnects | |
| Series MIL-DTL-26482, 851 Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 8-4 Shell Size, MIL | | Circular Connectors | |
| Connector TypePlug, Male PinsNumber of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A | Package | - | |
| Number of Positions4Shell Size - Insert8-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A | Series | MIL-DTL-26482, 851 | |
| Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp, Sealing Gland Voltage - Rated - Current Rating 7.5A | Connector Type | Plug, Male Pins | |
| Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp, Sealing Gland Voltage - Rated - Current Rating 7.5A | Number of Positions | 4 | |
| Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCable Clamp, Sealing GlandVoltage - Rated-Current Rating7.5A | Shell Size - Insert | 8-4 | |
| Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp, Sealing Gland Voltage - Rated - Current Rating 7.5A | Shell Size, MIL | - | |
| Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp, Sealing Gland Voltage - Rated - Current Rating 7.5A | Mounting Type | Free Hanging (In-Line) | |
| Orientation N (Normal) Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp, Sealing Gland Voltage - Rated - Current Rating 7.5A | Termination | Solder Cup | |
| Ingress Protection IP65/67 - Dust Tight, Water Resistant, Waterproof Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Cable Clamp, Sealing Gland Voltage - Rated - Current Rating 7.5A | Fastening Type | Bayonet Lock | |
| Shell Material, Finish Contact Finish Gold Features Cable Clamp, Sealing Gland Voltage - Rated - Current Rating 7.5A | Orientation | N (Normal) | |
| Contact Finish Gold Features Cable Clamp, Sealing Gland Voltage - Rated - Current Rating 7.5A | Ingress Protection | IP65/67 - Dust Tight, Water Resistant, Waterproof | |
| Features Cable Clamp, Sealing Gland Voltage - Rated - Current Rating 7.5A | Shell Material, Finish | Aluminum Alloy, Olive Drab Cadmium Plated | |
| Voltage - Rated - Current Rating 7.5A | Contact Finish | Gold | |
| Current Rating 7.5A | Features | Cable Clamp, Sealing Gland | |
| - | Voltage - Rated | - | |
| Report errors? | Current Rating | 7.5A | |
| | | Report errors | ? |

85106JC84P50 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

85106JC84P50 Payment Methods



















85106JC84P50 Shipping Methods













If you have any question about 85106JC84P50, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com