

8530631001 Information



For Reference Only

Part Number8530631001ManufacturerWeidmullerCategoryRelays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 10A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









8530631001 Specifications

Manufacturer Part Number8530631001ManufacturerWeidmullerCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesPRSRelay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current16.7mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time-Release Time-FeaturesLED IndicatorMounting TypeDIN RailTermination StyleScrew Terminal		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesPRSRelay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current16.7mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time-Release Time-FeaturesLED IndicatorMounting TypeDIN RailTermination StyleScrew Terminal	Manufacturer Part Number	8530631001
Package - Series PRS Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 16.7mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time - Release Time Features LED Indicator Mounting Type DIN Rail Termination Style Screw Terminal	Manufacturer	Weidmuller
Package-SeriesPRSRelay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current16.7mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time-Release Time-FeaturesLED IndicatorMounting TypeDIN RailTermination StyleScrew Terminal	Category	Relays
SeriesPRSRelay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current16.7mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time-Release Time-FeaturesLED IndicatorMounting TypeDIN RailTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current16.7mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time-Release Time-FeaturesLED IndicatorMounting TypeDIN RailTermination StyleScrew Terminal	Package	-
Coil TypeNon LatchingCoil Current16.7mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)10ASwitching Voltage250VAC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time-Release Time-FeaturesLED IndicatorMounting TypeDIN RailTermination StyleScrew Terminal	Series	PRS
Coil Current 16.7mA 24VDC 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time - Release Time - Features LED Indicator Mounting Type DIN Rail Termination Style Screw Terminal	Relay Type	General Purpose with Socket
Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time - Release Time - Features LED Indicator Mounting Type DIN Rail Termination Style	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time Release Time - Release Time LED Indicator Mounting Type DIN Rail Termination Style	Coil Current	16.7mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time - Release Time - Features LED Indicator Mounting Type DIN Rail Termination Style	Coil Voltage	24VDC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time - Release Time - Features LED Indicator Mounting Type DIN Rail Termination Style Screw Terminal	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time - Release Time - Features LED Indicator Mounting Type DIN Rail Termination Style 16.8 VDC 2.4 VDC DIN Rail Screw Terminal	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time - Release Time - Features LED Indicator Mounting Type DIN Rail Termination Style Screw Terminal	Switching Voltage	250VAC - Max
Operate Time Release Time LED Indicator Features LED Indicator Mounting Type DIN Rail Termination Style Screw Terminal	Turn On Voltage (Max)	16.8 VDC
Release Time - LED Indicator Mounting Type DIN Rail Termination Style Screw Terminal	Turn Off Voltage (Min)	2.4 VDC
Features LED Indicator Mounting Type DIN Rail Termination Style Screw Terminal	Operate Time	-
Mounting Type DIN Rail Termination Style Screw Terminal	Release Time	-
Termination Style Screw Terminal	Features	LED Indicator
·	Mounting Type	DIN Rail
Report errors?	Termination Style	Screw Terminal
		Report errors?

8530631001 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

8530631001 Payment Methods





















8530631001 Shipping Methods













If you have any question about 8530631001, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com