

### 860010272007 Information

www.com

For Reference Only

**Part Number** 860010272007

Manufacturer Wurth Electronics Inc.

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP 150 UF 20% 10 V

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **860010272007 Specifications**

Manufacturer Part Number         860010272007           Manufacturer         Wurth Electronics Inc.           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         WCAP-ATG8           Capacitance         150μF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         231mA @ 120Hz           Ripple Current - High Frequency         318.78mA @ 100kHz           Impedance         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole		
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         WCAP-ATG8           Capacitance         150µF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polar         Applications         General Purpose           Ripple Current - Low Frequency         23 Im A @ 120Hz           Ripple Current - High Frequency         318.78mA @ 100kHz           Impedance         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -	Manufacturer Part Number	860010272007
PackageRadial, CanSeriesWCAP-ATG8Capacitance150μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency231mA @ 120HzRipple Current - High Frequency318.78mA @ 100kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-	Manufacturer	Wurth Electronics Inc.
PackageRadial, CanSeriesWCAP-ATG8Capacitance150µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency231mA @ 120HzRipple Current - High Frequency318.78mA @ 100kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-	Category	Capacitors
Series         WCAP-ATG8           Capacitance         150μF           Tolerance         ±20%           Voltage - Rated         10V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         231mA @ 120Hz           Ripple Current - High Frequency         318.78mA @ 100kHz           Impedance         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -		Aluminum Electrolytic Capacitors
Capacitance       150µF         Tolerance       ±20%         Voltage - Rated       10V         ESR (Equivalent Series Resistance)       -         Lifetime @ Temp.       2000 Hrs @ 85°C         Operating Temperature       -40°C ~ 85°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       231mA @ 120Hz         Ripple Current - High Frequency       318.78mA @ 100kHz         Impedance       -         Lead Spacing       0.079" (2.00mm)         Size / Dimension       0.197" Dia (5.00mm)         Height - Seated (Max)       0.492" (12.50mm)         Surface Mount Land Size       -	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 10V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose Ripple Current - Low Frequency 231mA @ 120Hz  Ripple Current - High Frequency 318.78mA @ 100kHz  Impedance - Lead Spacing 0.079" (2.00mm)  Size / Dimension 0.197" Dia (5.00mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -	Series	WCAP-ATG8
Voltage - Rated 10V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose Ripple Current - Low Frequency 231mA @ 120Hz  Ripple Current - High Frequency 318.78mA @ 100kHz  Impedance - Lead Spacing 0.079" (2.00mm)  Size / Dimension 0.197" Dia (5.00mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -	Capacitance	150μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  318.78mA @ 100kHz  Impedance  Lead Spacing  0.079" (2.00mm)  Size / Dimension  0.197" Dia (5.00mm)  Height - Seated (Max)  Surface Mount Land Size  -	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 231mA @ 120Hz Ripple Current - High Frequency 318.78mA @ 100kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size -	Voltage - Rated	10V
Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  318.78mA @ 100kHz  Impedance  - Lead Spacing  0.079" (2.00mm)  Size / Dimension  0.197" Dia (5.00mm)  Height - Seated (Max)  0.492" (12.50mm)  Surface Mount Land Size  -	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 231mA @ 120Hz  Ripple Current - High Frequency 318.78mA @ 100kHz  Impedance -  Lead Spacing 0.079" (2.00mm)  Size / Dimension 0.197" Dia (5.00mm)  Height - Seated (Max) 0.492" (12.50mm)  Surface Mount Land Size -	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  318.78mA @ 120Hz  Impedance  Lead Spacing  0.079" (2.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  General Purpose  231mA @ 120Hz  318.78mA @ 100kHz  -  0.079" (2.00mm)  0.197" Dia (5.00mm)  -  Surface Mount Land Size  -	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  318.78mA @ 100kHz  Impedance  Lead Spacing  0.079" (2.00mm)  Size / Dimension  0.197" Dia (5.00mm)  Height - Seated (Max)  0.492" (12.50mm)  Surface Mount Land Size  -	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size -	Applications	General Purpose
Impedance         -           Lead Spacing         0.079" (2.00mm)           Size / Dimension         0.197" Dia (5.00mm)           Height - Seated (Max)         0.492" (12.50mm)           Surface Mount Land Size         -	Ripple Current - Low Frequency	231mA @ 120Hz
Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-	Ripple Current - High Frequency	318.78mA @ 100kHz
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-	Impedance	-
Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size -	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size -	Size / Dimension	0.197" Dia (5.00mm)
	Height - Seated (Max)	0.492" (12.50mm)
Mounting Type Through Hole	Surface Mount Land Size	-
	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

### 860010272007 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 860010272007 Payment Methods



















## 860010272007 Shipping Methods













If you have any question about 860010272007, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com