

860040275006

860040275006 Information



Part Number	860040275006	
Manufacturer	Wurth Electronics Inc.	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP 680 UF 20% 10 V	
Package	Radial, Can	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



860040275006 Specifications

Manufacturer Part Number860040275006Manufacturer AWurh Electronics Inc.CategoryCapacitorsAtuminum Electrolytic CapacitorsPackageRadial, CanStriesWCAP-ATULCapacitance680µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime Temp.6000 Hrs @ 105°COperating Temperature6000 Hrs @ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency800mA @ 100kHzIppedance0.0017°C (Somm)Sized Maxing0.394° Dia(Maxing)Sized Maxing0.394° Dia(Maxing)Sized Maxing-Manufacturet Lows Frequency0.5° (14.00mm)Sized Maxing0.5° (14.00mm)Sized Maxing0.5° (14.00mm)Sized Maxing5.° (14.00mm)Sized Maxing Xiae-Mounting TypeHrough HelePackage CaseKanga Case		
CategoryCapacitorsAluminum Electrolytic CapacitonsPackageRadial, CanSeriesWCAP-ATULCapacitance680µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Derating Temperature6000 Hrs @ 105°COperating Temperature6000 Hrs @ 100°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency800mA @ 100kHzImpedance85 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max).551" (14.00mm)Surface Mount Land Size-Nounting TypeFinogationPackage / CaseMain Quant CanaRipple Caree.551" (14.00mm)Stare Apple Caree.551" (15.00mm)Stare Apple Caree.551" (15.00mm)Stare Apple Caree.551"	Manufacturer Part Number	860040275006
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesWCAP-ATULCapacitance680µFTolerance±20%Voltage - RatedIOVESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature6000 Hrs @ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency600m A @ 120HzRipple Current - High Frequency800mA @ 100kHzImpedance55 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.551" (14.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Wurth Electronics Inc.
PackageRadial, CanSeriesWCAP-ATULCapacitance680µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency600m A @ 120HzImpedance850mA @ 100kHzLiad Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension0.551" (14.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Pouring TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesWCAP-ATULCapacitance680µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency600m A @ 120HzImpedance85 mOhmsLad Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila, Can		Aluminum Electrolytic Capacitors
Capacitance680µFTolerance±20%Voltage Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency600m A @ 120HzImpedanceS5 mOhmsLad Spacing0.197" (5.00mm)Siz / Dimension0.551" (14.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeHorage MathematicaPolace2.51" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePolaceStall AgeStarey CaseStall AgeStaley CaseStall AgeStaley CaseStall AgeStaley CaseStall AgeStaley CaseStall AgeStaley CaseStaley Case	Package	Radial, Can
Tolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency600m A @ 120HzImpedance85 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Series	WCAP-ATUL
Voltage - RatedIOVESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature- 40°C ~ 105°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency600mA @ 120HzRipple Current - High Frequency800mA @ 100kHzImpedance85 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.551" (14.00mm)Height - Seated (Max)-Mounting TypeThrough HolePackage / CaseRatial, Can	Capacitance	680µF
FormESR (Equivalent Series Resistance)-Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency600mA @ 120HzBipple Current - High Frequency800mA @ 100kHzImpedance85 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency600mA @ 120HzBippe Current - High Frequency800mA @ 100kHzImpedance85 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.551" (14.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeRadia, Can	Voltage - Rated	10V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency600mA @ 120HzBipple Current - High Frequency800mA @ 100kHzImpedance85 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max).551" (14.00mm)Surface Mount Land Size-Mounting TypeRadia, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency600mA @ 120HzRipple Current - High Frequency800mA @ 100kHzImpedance85 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	6000 Hrs @ 105°C
ApplicationsGeneral PurposeApplicationsGomA @ 120HzRipple Current - Low Frequency800mA @ 100kHzMipedance85 mOhnsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency600mA @ 120HzRipple Current - High Frequency800mA @ 100kHzImpedance85 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency800mA @ 100kHzImpedance85 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance85 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	600mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	800mA @ 100kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	85 mOhms
Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.551" (14.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

860040275006 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

860040275006 Payment Methods



860040275006 Shipping Methods



If you have any question about 860040275006, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com