

860040475011

860040475011 Information



Part Number	860040475011	
Manufacturer	Wurth Electronics Inc.	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP 1000 UF 20% 25 V	
Package	Radial, Can	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



860040475011 Specifications

Manufacturer Part Number86004075011ManufacturerWurh Electronics Inc.CategoryCapacitorsAluminum Electrolytic CapacitonsPackageRadial, CanSeriesWCAP-ATULCapacitance1000µFTolerance±20%Voltage - Rated5-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature40°C ~ 105°COplaring Temperature6-ApplicationsGeneral PurposeRipple Current - High Frequency1.365A @ 120HzImpedance32 mOhmsLided Spacing0.197" (S.00mm)Size / Dimension0.394" Dia (10.00mm)Hight - Seated (Max).Munting TypeThrough HoleNouting TypeThrough HolePanet manufacture of the seater of the s		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesWCAP-ATULCapacitance1000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.365A @ 120HzImpedance32 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	860040475011
Auminum Electrolytic CapacitorsPackageRadial, CanSeriesWCAP-ATULCapacitance1000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplications32 mOhmsRipple Current - Low Frequency1.365A @ 120HzImpedance32 mOhmsLaed Spacing0.197" (5.0mm)Size / Dimension1.240" (31.50mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Wurth Electronics Inc.
PackageRadial, CanSeriesWCAP-ATULCapacitance1000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplications32 MOhmsRipple Current - Low Frequency1.365A @ 120HzImpedance0.197" (5.00mm)Liad Spacing0.394" Dia (10.00mm)Size / Dimension1.240" (31.50mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesWCAP-ATULCapacitance1000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperaturee40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency1.365A @ 120HzImpedance32 mOhmsSize / Dimension0.394" Dia (10.00mm)Size / Dimension1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia (Can		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.365A @ 120HzInpedance32 mOhmsSize / Dimension0.197" (5.00mm)Size / Dimension1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.365A @ 120HzInpedance32 mOhmsLead Spacing0.197" (5.00mm)Size / Dinension0.394" Dia (10.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can	Series	WCAP-ATUL
Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.365A @ 120HzRipple Current - High Frequency1.82A @ 100kHzImpedance32 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	1000µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.365A @ 120HzRipple Current - High Frequency1.82A @ 100kHzImpedance32 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension1.240" (31.50mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.7000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.365A @ 120HzRipple Current - High Frequency1.82A @ 100kHzImpedance32 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	25V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.365A @ 120HzRipple Current - High Frequency1.82A @ 100kHzImpedance32 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.365A @ 120HzRipple Current - High Frequency1.82A @ 100kHzImpedance32 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	7000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.365A @ 120HzRipple Current - High Frequency1.82A @ 100kHzImpedance32 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency1.365A @ 120HzRipple Current - High Frequency1.82A @ 100kHzImpedance32 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency1.82A @ 100kHzImpedance32 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance32 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1.365A @ 120Hz
I card Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.82A @ 100kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	32 mOhms
Height - Seated (Max)1.240" (31.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.240" (31.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Deport errors	Package / Case	Radial, Can
Keport errors		Report errors?

860040475011 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

860040475011 Payment Methods



860040475011 Shipping Methods



If you have any question about 860040475011, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com