

860130874006 Information

www.h. er.com

For Reference Only

Part Number 860130874006

Manufacturer Wurth Electronics Inc.

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP 10 UF 20% 100 V

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









860130874006 Specifications

Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series WCAP-ATET Capacitance 10µF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 102mA @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size -		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can WCAP-ATET Capacitance I0µF Tolerance ±20% Voltage - Rated I00V ESR (Equivalent Series Resistance) Lifetime @ Temp. I000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Journal of Mark (3.50mm) Size / Dimension Lieight - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can	Manufacturer Part Number	860130874006
Package Radial, Can Series WCAP-ATET Capacitance 10μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 102mA @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Wurth Electronics Inc.
Package Radial, Can Series WCAP-ATET Capacitance 10μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 102mA @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series WCAP-ATET Capacitance 10μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 102mA @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 10μF Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 102mA @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 100V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 102mA @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	WCAP-ATET
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 125°C -40°C ~ 125°C Operating Temperature -40°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 102mA @ 120Hz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Capacitance	10μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 102mA @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 102mA @ 120Hz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 125°C -40°C ~ 125°C -40	Voltage - Rated	100V
Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 102mA @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 102mA @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	1000 Hrs @ 125°C
Applications General Purpose Ripple Current - Low Frequency 60mA @ 120Hz Ripple Current - High Frequency 102mA @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 125°C
Ripple Current - Low Frequency Ripple Current - High Frequency 102mA @ 100kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	60mA @ 120Hz
Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	102mA @ 100kHz
Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.512" (13.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.315" Dia (8.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.512" (13.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
•		Report errors?

860130874006 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

860130874006 Payment Methods



















860130874006 Shipping Methods













If you have any question about 860130874006, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com