

### 860131275004 Information

www.b.er.com

For Reference Only

**Part Number** 860131275004

Manufacturer Wurth Electronics Inc.

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP 4.7 UF 20% 350 V

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **860131275004 Specifications**

Manufacturer Part Number         860131275004           Manufacturer         Wurth Electronics Inc.           Category         Capacitors           Package         Radial, Can           Series         WCAP-ATET           Capacitance         4.7µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 125°C           Operating Temperature         -25°C ~ 125°C           Polarization         General Purpose           Ripple Current - Low Frequency         68mA @ 120Hz           Ripple Current - High Frequency         115.6mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.689" (17.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		
Category         Capacitors           Package         Radial, Can           Series         WCAP-ATET           Capacitance         4.7μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 125°C           Operating Temperature         -25°C ~ 125°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         68mA @ 120Hz           Ripple Current - High Frequency         115.6mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.689" (17.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	860131275004
Aluminum Electrolytic Capacitors  Package Radial, Can  Series WCAP-ATET  Capacitance 4.7µF  Tolerance ±20%  Voltage - Rated 350V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 125°C  Operating Temperature -25°C ~ 125°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 68mA @ 120Hz  Ripple Current - High Frequency 115.6mA @ 100kHz  Impedance - Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.689" (17.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Manufacturer	Wurth Electronics Inc.
Package         Radial, Can           Series         WCAP-ATET           Capacitance         4.7μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 125°C           Operating Temperature         -25°C ~ 125°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         68mA @ 120Hz           Ripple Current - High Frequency         115.6mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.689" (17.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         WCAP-ATET           Capacitance         4.7µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 125°C           Operating Temperature         -25°C ~ 125°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         68mA @ 120Hz           Ripple Current - High Frequency         115.6mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.689" (17.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         4.7µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 125°C           Operating Temperature         -25°C ~ 125°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         68mA @ 120Hz           Ripple Current - High Frequency         115.6mA @ 100kHz           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.689" (17.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 350V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 125°C  Operating Temperature -25°C ~ 125°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 68mA @ 120Hz  Ripple Current - High Frequency 115.6mA @ 100kHz  Impedance - Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.689" (17.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	WCAP-ATET
Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature-25°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency68mA @ 120HzRipple Current - High Frequency115.6mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	4.7μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 125°C  Operating Temperature  -25°C ~ 125°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  68mA @ 120Hz  Ripple Current - High Frequency  115.6mA @ 100kHz  Impedance  -  Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.394" Dia (10.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -25°C ~ 125°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  115.6mA @ 120Hz  Impedance  - Lead Spacing  0.197" (5.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  2000 Hrs @ 125°C  -25°C ~ 125°C  Roll Turent  -25°C ~ 125°C  -25°C  -25°C ~ 125°C  -25°C  -25	Voltage - Rated	350V
Operating Temperature -25°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 68mA @ 120Hz Ripple Current - High Frequency 115.6mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 68mA @ 120Hz  Ripple Current - High Frequency 115.6mA @ 100kHz  Impedance -  Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.689" (17.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 125°C
Applications  General Purpose  Ripple Current - Low Frequency  68mA @ 120Hz  Ripple Current - High Frequency  115.6mA @ 100kHz  Impedance  - Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.394" Dia (10.00mm)  Height - Seated (Max)  0.689" (17.50mm)  Surface Mount Land Size  - Mounting Type  Through Hole  Package / Case  Radial, Can	Operating Temperature	-25°C ~ 125°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  115.6mA @ 100kHz  Impedance  - Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.394" Dia (10.00mm)  Height - Seated (Max)  0.689" (17.50mm)  Surface Mount Land Size  - Mounting Type  Through Hole  Package / Case  Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	68mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	115.6mA @ 100kHz
Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.689" (17.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.689" (17.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### 860131275004 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **860131275004 Payment Methods**



















### **860131275004 Shipping Methods**













If you have any question about 860131275004, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com