

## 860160575025 Information

**Part Number** 860160575025

Manufacturer Wurth Electronics Inc.

Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP 470 UF 20% 35 V

Package Radial, Can

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **860160575025 Specifications**

Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         WCAP-ATLL           Capacitance         470μF           Tolerance         ±20%           Voltage - Rated         35 V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         6000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         755.16mA @ 120Hz           Ripple Current - High Frequency         1.302A @ 100kHz           Impedance         110 mOhms           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.846" (21.50mm)           Surface Mount Land Size         -		
Category         Capacitors           Package         Radial, Can           Series         WCAP-ATLL           Capacitance         470μF           Tolerance         ±20%           Voltage - Rated         35V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         6000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         755.16mA @ 120Hz           Ripple Current - High Frequency         1.302A @ 100kHz           Impedance         110 mOhms           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.846" (21.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	860160575025
Package         Radial, Can           Series         WCAP-ATLL           Capacitance         470µF           Tolerance         ±20%           Voltage - Rated         35 V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         6000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         755.16mA @ 120Hz           Ripple Current - High Frequency         1.302A @ 100kHz           Impedance         110 mOhms           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.846" (21.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer	Wurth Electronics Inc.
Package         Radial, Can           Series         WCAP-ATLL           Capacitance         470μF           Tolerance         ±20%           Voltage - Rated         35V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         6000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         755.16mA @ 120Hz           Ripple Current - High Frequency         1.302A @ 100kHz           Impedance         110 mOhms           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.846" (21.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         WCAP-ATLL           Capacitance         470µF           Tolerance         ±20%           Voltage - Rated         35 V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         6000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         755.16mA @ 120Hz           Ripple Current - High Frequency         1.302A @ 100kHz           Impedance         110 mOhms           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.394" Dia (10.00mm)           Height - Seated (Max)         0.846" (21.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance       470μF         Tolerance       ±20%         Voltage - Rated       35V         ESR (Equivalent Series Resistance)       -         Lifetime @ Temp.       6000 Hrs @ 105°C         Operating Temperature       -55°C ~ 105°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       755.16mA @ 120Hz         Ripple Current - High Frequency       1.302A @ 100kHz         Impedance       110 mOhms         Lead Spacing       0.197" (5.00mm)         Size / Dimension       0.394" Dia (10.00mm)         Height - Seated (Max)       0.846" (21.50mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 35V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 6000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 755.16mA @ 120Hz  Ripple Current - High Frequency 1.302A @ 100kHz  Impedance 110 mOhms  Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.846" (21.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	WCAP-ATLL
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  6000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.302A @ 100kHz  Impedance  110 mOhms  Lead Spacing  0.197" (5.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  R6000 Hrs @ 105°C  -55°C ~ 105°C  General Purpose  General Purpose  1.302A @ 120Hz  1.302A @ 120Hz  1.302A @ 100kHz  1.302A @ 100kHz	Capacitance	470μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  6000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  755.16mA @ 120Hz  Ripple Current - High Frequency  1.302A @ 100kHz  Impedance  110 mOhms  Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.394" Dia (10.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.302A @ 100kHz  Impedance  110 mOhms  Lead Spacing  0.197" (5.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  6000 Hrs @ 105°C  -55°C ~ 105°C  Roneral Purpose  755.16mA @ 120Hz  1.302A @ 100kHz  1.302A @ 100k	Voltage - Rated	35V
Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 755.16mA @ 120Hz Ripple Current - High Frequency 1.302A @ 100kHz Impedance 110 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - Low Frequency Ripple Cur	Lifetime @ Temp.	6000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 755.16mA @ 120Hz Ripple Current - High Frequency 1.302A @ 100kHz Impedance 110 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  1.302A @ 100kHz  Impedance  110 mOhms  Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.394" Dia (10.00mm)  Height - Seated (Max)  0.846" (21.50mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Polarization	Polar
Ripple Current - High Frequency  1.302A @ 100kHz  Impedance  110 mOhms  Lead Spacing  0.197" (5.00mm)  Size / Dimension  0.394" Dia (10.00mm)  Height - Seated (Max)  0.846" (21.50mm)  Surface Mount Land Size  - Mounting Type  Through Hole  Package / Case  Radial, Can	Applications	General Purpose
Impedance 110 mOhms  Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.846" (21.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Ripple Current - Low Frequency	755.16mA @ 120Hz
Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.846" (21.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Ripple Current - High Frequency	1.302A @ 100kHz
Size / Dimension 0.394" Dia (10.00mm)  Height - Seated (Max) 0.846" (21.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	110 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.846" (21.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

### 860160575025 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **860160575025 Payment Methods**



















### **860160575025 Shipping Methods**













If you have any question about 860160575025, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com