

861-83-043-10-001101 Information



For Reference Only

Part Number 861-83-043-10-001101

Manufacturer Preci-Dip

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description PCB CONN SOLDER TAIL 1MM

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









861-83-043-10-001101 Specifications

| Manufacturer Part Number 861-83-043-10-001101 Manufacturer Preci-Dip Category Connectors, Interconnects Package - Series 861 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 43 Number of Positions Loaded All Pitch - Mating 0.039" (1.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Testening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.098" (2.50mm) Operating Temperature -55°C ~ 125°C Material Flammability Rating UL94 V-0 | | |
|--|-----------------------------------|---|
| Category Connectors, Interconnects Package - Series 861 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 43 Number of Positions Loaded All Pitch - Mating 0.039" (1.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Pastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.098" (2.50mm) Contact Length - Post 0.098" (2.50mm) Operating Temperature -55°C ~ 125°C | Manufacturer Part Number | 861-83-043-10-001101 |
| Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series 861 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 43 Number of Positions Loaded Pitch - Mating Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height Contact Length - Post Operating Temperature -55°C ~ 125°C | Manufacturer | Preci-Dip |
| Package - Series 861 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 43 Number of Positions Loaded All Pitch - Mating 0.039" (1.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5µin (0.75µm) Insulation Color Black Insulation Height 0.098" (2.50mm) Contact Length - Post 0.098" (2.50mm) Operating Temperature -55°C ~ 125°C | Category | Connectors, Interconnects |
| Series 861 Connector Type Socket Contact Type Female Socket Style Board to Board Number of Positions 43 Number of Positions Loaded All Pitch - Mating 0.039" (1.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5μin (0.75μm) Insulation Color Black Insulation Height 0.098" (2.50mm) Contact Length - Post 0.098" (2.50mm) Operating Temperature -55°C ~ 125°C | | Rectangular Connectors - Headers, Receptacles, Female Sockets |
| Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions43Number of Positions LoadedAllPitch - Mating $0.039"(1.00mm)$ Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating 29.5μ in $(0.75\mu$ m)Insulation ColorBlackInsulation Height $0.098"(2.50mm)$ Contact Length - Post $0.098"(2.50mm)$ Operating Temperature $-55°C \sim 125°C$ | Package | - |
| Contact TypeFemale SocketStyleBoard to BoardNumber of Positions43Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.098" (2.50mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C | Series | 861 |
| StyleBoard to BoardNumber of Positions43Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5µin (0.75µm)Insulation ColorBlackInsulation Height0.098" (2.50mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C | Connector Type | Socket |
| Number of Positions43Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.098" (2.50mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C | Contact Type | Female Socket |
| Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.098" (2.50mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C | Style | Board to Board |
| Pitch - Mating0.039" (1.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.098" (2.50mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C | Number of Positions | 43 |
| Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.098" (2.50mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C | Number of Positions Loaded | All |
| Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.098" (2.50mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C | Pitch - Mating | 0.039" (1.00mm) |
| Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating29.5μin (0.75μm)Insulation ColorBlackInsulation Height0.098" (2.50mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C | Number of Rows | 1 |
| Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5μin (0.75μm) Insulation Color Black Insulation Height 0.098" (2.50mm) Contact Length - Post 0.098" (2.50mm) Operating Temperature -55°C ~ 125°C | Row Spacing - Mating | - |
| Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.098" (2.50mm) Contact Length - Post 0.098" (2.50mm) Operating Temperature -55°C ~ 125°C | Mounting Type | Through Hole |
| Contact Finish - Mating Gold Contact Finish Thickness - Mating 29.5 μ in (0.75 μ m) Insulation Color Black Insulation Height 0.098" (2.50mm) Contact Length - Post 0.098" (2.50mm) Operating Temperature -55°C ~ 125°C | Termination | Solder |
| Contact Finish Thickness - Mating $29.5\mu in (0.75\mu m)$ Insulation Color Black Insulation Height $0.098'' (2.50mm)$ Contact Length - Post $0.098'' (2.50mm)$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ | Fastening Type | Push-Pull |
| Insulation Color Black Insulation Height 0.098" (2.50mm) Contact Length - Post 0.098" (2.50mm) Operating Temperature -55°C ~ 125°C | Contact Finish - Mating | Gold |
| Insulation Height $0.098" (2.50mm)$ Contact Length - Post $0.098" (2.50mm)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Contact Finish Thickness - Mating | 29.5μin (0.75μm) |
| Contact Length - Post $0.098" (2.50mm)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Insulation Color | Black |
| Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Insulation Height | 0.098" (2.50mm) |
| | Contact Length - Post | 0.098" (2.50mm) |
| Material Flammability Rating UL94 V-0 | Operating Temperature | -55°C ~ 125°C |
| | Material Flammability Rating | UL94 V-0 |

| Contact Finish - Post | Tin |
|------------------------|----------------|
| Mated Stacking Heights | - |
| Ingress Protection | - |
| Features | - |
| | Report errors? |

861-83-043-10-001101 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

861-83-043-10-001101 Payment Methods



















861-83-043-10-001101 Shipping Methods













If you have any question about 861-83-043-10-001101, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com