



### 861011485015 Information



For Reference Only

**Part Number** 861011485015

Manufacturer Wurth Electronics Inc.

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 180UF 20% 450V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **861011485015 Specifications**

Manufacturer Part Number         861011485015           Manufacturer         Wurth Electronics Inc.           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In           Series         WCAP-AIG8           Capacitance         180μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.52A @ 120Hz           Ripple Current - High Frequency         2.0976A @ 100kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.496" (38.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	_	
Category         Capacitors           Package         Radial, Can - Snap-In           Series         WCAP-AIG8           Capacitance         180µF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.52A @ 120Hz           Ripple Current - High Frequency         2.0976A @ 100kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.496" (38.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Manufacturer Part Number	861011485015
Package         Radial, Can - Snap-In           Series         WCAP-AIG8           Capacitance         180µF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.52A @ 120Hz           Ripple Current - High Frequency         2.0976A @ 100kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.496" (38.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Manufacturer	Wurth Electronics Inc.
Package         Radial, Can - Snap-In           Series         WCAP-AIG8           Capacitance         180μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.52A @ 120Hz           Ripple Current - High Frequency         2.0976A @ 100kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.496" (38.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Category	Capacitors
Series         WCAP-AIG8           Capacitance         180μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.52A @ 120Hz           Ripple Current - High Frequency         2.0976A @ 100kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.496" (38.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance       180μF         Tolerance       ±20%         Voltage - Rated       450V         ESR (Equivalent Series Resistance)       -         Lifetime @ Temp.       2000 Hrs @ 85°C         Operating Temperature       -25°C ~ 85°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       1.52A @ 120Hz         Ripple Current - High Frequency       2.0976A @ 100kHz         Impedance       -         Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.181" Dia (30.00mm)         Height - Seated (Max)       1.496" (38.00mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20%  Voltage - Rated 450V  ESR (Equivalent Series Resistance)	Series	WCAP-AIG8
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  2.0976A @ 120Hz  Impedance  -  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Capacitance	180μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  1.52A @ 120Hz  Ripple Current - High Frequency  2.0976A @ 100kHz  Impedance  - Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  1.496" (38.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  1.52A @ 120Hz  Ripple Current - High Frequency  2.0976A @ 100kHz  Impedance  - Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  1.496" (38.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.52A @ 120Hz Ripple Current - High Frequency 2.0976A @ 100kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.496" (38.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.52A @ 120Hz  Ripple Current - High Frequency 2.0976A @ 100kHz  Impedance -  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.496" (38.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 1.52A @ 120Hz Ripple Current - High Frequency 2.0976A @ 100kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.496" (38.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 2.0976A @ 100kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.496" (38.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency  2.0976A @ 100kHz  Impedance - Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  1.496" (38.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Applications	General Purpose
Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.496" (38.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - Low Frequency	1.52A @ 120Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.496" (38.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - High Frequency	2.0976A @ 100kHz
Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.496" (38.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.496" (38.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors

### 861011485015 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **861011485015 Payment Methods**



















## **861011485015 Shipping Methods**













If you have any question about 861011485015, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com