

865080240003 Information

Part Number 865080240003

Manufacturer Wurth Electronics Inc.

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP 33 UF 20% 10 V Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









865080240003 Specifications

Manufacturer Part Number 865080240003 Manufacturer Wurth Electronics Inc. Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series WCAP-ASLI Capacitance 33µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 58.5mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance 1.85 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series WCAP-ASLI Capacitance 33μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Oparing Temperature -55°C ~ 105°C Polar Applications General Purpose Ripple Current - Low Frequency 58.5mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance 1.85 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer Part Number	865080240003
Package Radial, Can - SMD Series WCAP-ASLI Capacitance 33μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 58.5mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance 1.85 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer	Wurth Electronics Inc.
Package Radial, Can - SMD Series WCAP-ASLI Capacitance 33μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 58.5mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance 1.85 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Category	Capacitors
Series WCAP-ASLI Capacitance 33µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 58.5mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance 1.85 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD		Aluminum Electrolytic Capacitors
Capacitance 33µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 58.5mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance 1.85 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Package	Radial, Can - SMD
Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 58.5mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance 1.85 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Series	WCAP-ASLI
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency St.5mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance 1.85 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Package / Case Radial, Can - SMD	Capacitance	33μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 58.5mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance 1.85 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 828.5mA @ 120Hz Ripple Current - High Frequency 90mA @ 100kHz Impedance 1.85 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Voltage - Rated	10V
Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 90mA @ 120Hz Rippedance 1.85 Ohms Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Package / Case Radial, Can - SMD	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency S8.5mA @ 120Hz Ripple Current - High Frequency Polar @ 100kHz Impedance 1.85 Ohms Lead Spacing - Size / Dimension O.157" Dia (4.00mm) Height - Seated (Max) Surface Mount Land Size O.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case General Purpose 58.5mA @ 120Hz 90mA @ 100kHz 1.85 Ohms - 1.85 Ohms - 0.157" Dia (4.00mm) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm)	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 90mA @ 100kHz Impedance 1.85 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Polarization	Polar
Ripple Current - High Frequency 90mA @ 100kHz Impedance 1.85 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Applications	General Purpose
Impedance 1.85 Ohms Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - Low Frequency	58.5mA @ 120Hz
Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - High Frequency	90mA @ 100kHz
Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Impedance	1.85 Ohms
Height - Seated (Max) Surface Mount Land Size 0.217" (5.50mm) 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Lead Spacing	-
Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Size / Dimension	0.157" Dia (4.00mm)
Mounting Type Surface Mount Package / Case Radial, Can - SMD	Height - Seated (Max)	0.217" (5.50mm)
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.169" L x 0.169" W (4.30mm x 4.30mm)
	Mounting Type	Surface Mount
Report errors?	Package / Case	Radial, Can - SMD
		Report errors?

865080240003 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

865080240003 Payment Methods


































If you have any question about 865080240003, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com