

865080249010 Information

Part Number 865080249010

Manufacturer Wurth Electronics Inc.

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP 220 UF 20% 10 V **Package** Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









865080249010 Specifications

Manufacturer Part Number 865080249010 Manufacturer Wurth Electronics Inc. Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series WCAP-ASLI Capacitance 220µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 185.25mA @ 120Hz Ripple Current - High Frequency 285mA @ 100kHz Impedance 400 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.256" (6.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	•	
Category Capacitors Package Radial, Can - SMD Series WCAP-ASLI Capacitance 220µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 185.25mA @ 120Hz Ripple Current - High Frequency 285mA @ 100kHz Impedance 400 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.256" (6.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer Part Number	865080249010
Package Radial, Can - SMD Series WCAP-ASLI Capacitance 220μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 185.25mA @ 120Hz Ripple Current - High Frequency 285mA @ 100kHz Impedance 400 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.256" (6.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer	Wurth Electronics Inc.
Package Radial, Can - SMD Series WCAP-ASLI Capacitance 220µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 185.25mA @ 120Hz Ripple Current - High Frequency 285mA @ 100kHz Impedance 400 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.256" (6.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Category	Capacitors
Series WCAP-ASLI Capacitance 220μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 185.25mA @ 120Hz Ripple Current - High Frequency 285mA @ 100kHz Impedance 400 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.256" (6.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD		Aluminum Electrolytic Capacitors
Capacitance 220μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 185.25mA @ 120Hz Ripple Current - High Frequency 285mA @ 100kHz Impedance 400 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.256" (6.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Package	Radial, Can - SMD
Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 185.25mA @ 120Hz Ripple Current - High Frequency 285mA @ 100kHz Impedance 400 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.256" (6.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Series	WCAP-ASLI
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 285mA @ 120Hz Ripple Current - High Frequency 400 mOhms Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Capacitance	220μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 185.25mA @ 120Hz Ripple Current - High Frequency 285mA @ 100kHz Impedance 400 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.256" (6.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 185.25mA @ 120Hz Ripple Current - High Frequency 285mA @ 100kHz Impedance 400 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Voltage - Rated	10V
Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 285mA @ 120Hz Rippedance 400 mOhms Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Package / Case Radial, Can - SMD	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Research Re	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 285mA @ 120Hz Ripple Current - High Frequency 285mA @ 100kHz Impedance 400 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.256" (6.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 285mA @ 120Hz Manager	Polarization	Polar
Ripple Current - High Frequency 285mA @ 100kHz Impedance 400 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.256" (6.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Applications	General Purpose
Impedance 400 mOhms Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.256" (6.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - Low Frequency	185.25mA @ 120Hz
Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.256" (6.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - High Frequency	285mA @ 100kHz
Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.256" (6.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Impedance	400 mOhms
Height - Seated (Max) Surface Mount Land Size 0.256" (6.50mm) 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Lead Spacing	-
Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Size / Dimension	0.315" Dia (8.00mm)
Mounting Type Surface Mount Package / Case Radial, Can - SMD	Height - Seated (Max)	0.256" (6.50mm)
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.327" L x 0.327" W (8.30mm x 8.30mm)
	Mounting Type	Surface Mount
Report errors?	Package / Case	Radial, Can - SMD
		Report errors

865080249010 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

865080249010 Payment Methods



















865080249010 Shipping Methods













If you have any question about 865080249010, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com