

### **865230640003 Information**

**Part Number** 865230640003

Manufacturer Wurth Electronics Inc.

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP 0.33 UF 20% 50 V **Package** Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **865230640003 Specifications**

Manufacturer Part Number865230640003ManufacturerWurth Electronics Inc.CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesWCAP-AS5HCapacitance0.33µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.2mA @ 120HzRipple Current - High Frequency4.8mA @ 10kHz
Category Capacitors Aluminum Electrolytic Capacitors  Package Radial, Can - SMD  WCAP-AS5H Capacitance 0.33µF  Tolerance ±20%  Voltage - Rated 50V  ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C  Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency 4.8mA @ 10kHz
PackageRadial, Can - SMDSeriesWCAP-AS5HCapacitance0.33μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.2mA @ 120HzRipple Current - High Frequency4.8mA @ 10kHz
PackageRadial, Can - SMDSeriesWCAP-AS5HCapacitance0.33μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.2mA @ 120HzRipple Current - High Frequency4.8mA @ 10kHz
SeriesWCAP-AS5HCapacitance0.33μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.2mA @ 120HzRipple Current - High Frequency4.8mA @ 10kHz
Capacitance $0.33\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $50V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $5000  \text{Hrs @ 105°C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $3.2\text{mA @ 120Hz}$ Ripple Current - High Frequency $4.8\text{mA @ 10kHz}$
Tolerance ±20%  Voltage - Rated 50V  ESR (Equivalent Series Resistance) -  Lifetime @ Temp. 5000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 3.2mA @ 120Hz  Ripple Current - High Frequency 4.8mA @ 10kHz
Voltage - Rated 50V  ESR (Equivalent Series Resistance) -  Lifetime @ Temp. 5000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 3.2mA @ 120Hz  Ripple Current - High Frequency 4.8mA @ 10kHz
ESR (Equivalent Series Resistance)  Lifetime @ Temp. 5000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 3.2mA @ 120Hz  Ripple Current - High Frequency 4.8mA @ 10kHz
Lifetime @ Temp. 5000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 3.2mA @ 120Hz  Ripple Current - High Frequency 4.8mA @ 10kHz
Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  3.2mA @ 120Hz  Ripple Current - High Frequency  4.8mA @ 10kHz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 3.2mA @ 120Hz  Ripple Current - High Frequency 4.8mA @ 10kHz
Applications General Purpose Ripple Current - Low Frequency 3.2mA @ 120Hz Ripple Current - High Frequency 4.8mA @ 10kHz
Ripple Current - Low Frequency  3.2mA @ 120Hz  Ripple Current - High Frequency  4.8mA @ 10kHz
Ripple Current - High Frequency 4.8mA @ 10kHz
Impedance -
Lead Spacing -
Size / Dimension 0.157" Dia (4.00mm)
Height - Seated (Max) 0.217" (5.50mm)
Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm)
Mounting Type Surface Mount
Package / Case Radial, Can - SMD
Report errors?

### 865230640003 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **865230640003 Payment Methods**



















## 865230640003 Shipping Methods













If you have any question about 865230640003, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com