

865250642008

865250642008 Information

	Part Number	865250642008
ALE	Manufacturer	Wurth Electronics Inc.
www ene com	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP 4.7 UF 20% 50 V
	Package	Radial, Can - SMD
		For the pricing/inventory/lead time, please contact us
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



865250642008 Specifications

Manufacturer Wurth Electronics Inc. Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series WCAP-ASNP Capacitance 4.7µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency 30mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.217" (5.50mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm)		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - SMDPackageKadial, Can - SMDSeriesWCAP-ASNPCapacitance4.7µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature000 Hrs @ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency30mA @ 100kHzRipple Current - High Frequency30mA @ 100kHzImpedance-Lief Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Package / CaseRadial, Can - SMD	Manufacturer Part Number	865250642008
Aluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesWCAP-ASNPCapacitance4.7μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency20mA @ 120HzRipple Current - High Frequency30mA @ 100kHzSize / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Package / CaseRadial, Can - SMD	Manufacturer	Wurth Electronics Inc.
PackageRadial, Can - SMDSeriesWCAP-ASNPCapacitance4.7µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency20mA @ 120HzRipple Current - High Frequency30mA @ 100kHzSize / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Package / CaseRadial, Can - SMD	Category	Capacitors
SeriesWCAP-ASNPCapacitance4.7µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency20mA @ 120HzRipple Current - High Frequency30mA @ 100kHzImpedance-Lied Spacing0.197" Dia (5.00mm)Size / Dimension0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Package / CaseRadial, Can - SMD		Aluminum Electrolytic Capacitors
Capacitance4.7µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency30mA @ 100kHzImpedance-Lied Spacing0.197° Dia (5.00mm)Size / Dimension0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Package / CaseRadial, Can - SMD	Package	Radial, Can - SMD
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20mA @ 120Hz Binpedance - Lied Spacing - Size / Dimension 0.197" Dia (5.00mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Series	WCAP-ASNP
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency20mA @ 120HzBinpedance-Lead Spacing0.197" Dia (5.00mm)Size / Dimension0.209" L x 0.209" W (5.30mm x 5.30mm)Burface Mount Land SizeSurface MountPackage / CaseRatial, Can - SMD	Capacitance	4.7µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency20mA @ 120HzBinpedance-Lead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.209" L x 0.209" W (5.30mm x 5.30mm)Surface Mount Land SizeSurface MountPackage / CaseRaijal, Can - SMD	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency20mA @ 120HzBipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing0.197" Dia (5.00mm)Size / Dimension0.217" (5.50mm)Height - Seated (Max)0.209" L x 0.209" W (5.30mm x 5.30mm)Surface Mount Land SizeSurface MountPackage / CaseRadial, Can - SMD	Voltage - Rated	50V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency20mA @ 120HzBipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.209" L x 0.209" W (5.30mm x 5.30mm)Surface Mount Land SizeSurface MountPackage / CaseRadial, Can - SMD	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency20mA @ 120HzBipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency20mA @ 120HzRipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency20mA @ 120HzRipple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Polarization	Polar
Ripple Current - High Frequency30mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Applications	General Purpose
In resolution-Impedance-Lead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Ripple Current - Low Frequency	20mA @ 120Hz
Lead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Ripple Current - High Frequency	30mA @ 100kHz
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Impedance	-
Height - Seated (Max)0.217" (5.50mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Lead Spacing	-
Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Size / Dimension	0.197" Dia (5.00mm)
Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Height - Seated (Max)	0.217" (5.50mm)
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.209" L x 0.209" W (5.30mm x 5.30mm)
-	Mounting Type	Surface Mount
Report errors?	Package / Case	Radial, Can - SMD
		Report erro

865250642008 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

865250642008 Payment Methods WIRE PayPai Methods 865250642008 Shipping Methods ECHICA FEELS. IS ONO INFO

If you have any question about 865250642008, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com