

8657O25S065TLF

8657O25S065TLF Information

Heisener.com	 8657O25S065TLF Amphenol FCI Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 25POS STR IDC - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



8657O25S065TLF Specifications

Manufacturer Part Number86570258065TLFManufacturerAmphenol FCICategoryConnectors, InterconnectsD-Sub ConnectorsD-Sub ConnectorsPackage-Series8657Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows3 (DB, B)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureCable Side (4-40)Flange FeaturesFeed Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Contact Finish		
CategoryConnectors, Interconnects D-Sub ConnectorsPackage-Series8657Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows3 (DB, B)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureCable Side (4-40)FeaturesFeed Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Metrial Flammability Rating-Metrial Flammability Rating-	Manufacturer Part Number	8657O25S065TLF
PackageD-Sub ConnectorsPackage-Series8657Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector LayoutSignalContact TypeFree Hanging (In-Line)Flange FeatureCable Side (4-40)FeaturesSteel, Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Metrial Flammability Rating-Steel Flammability Rating-	Manufacturer	Amphenol FCI
Package-Series8657Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows3 (DB, B)Contact TypeSignalMounting TypeSignal (In-Line)Flange FeatureCoble Side (4-40)FeaturesSide Side (4-40)Shell Material, FinishSide (A-40)Contact FinishSide (1-200)Contact FinishSide (1-200)Shell Material, FinishSide (1-200)Contact Finish Thickness-Atterial Flammability Rating-Metrial Flammability Rating-Stell Flammability Rating-Stell Flammability Rating-Stell Stell St	Category	Connectors, Interconnects
Series8657Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows3 (DB, B)Shell Size, Connector LayoutSignalContact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureCable Side (4-40)FeaturesFeed Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability Rating-Steil Flammability Rating-		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows3 (DB, B)Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureCable Side (4-40)TerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability Rating-	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureCable Side (4-40)TerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability Rating-	Series	8657
Number of Positions25Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureCable Side (4-40)TerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact Finish Thickness-Ingress Protection-Material Flammability Rating-	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureCable Side (4-40)TerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability Rating-Contact Finish-Contact Finish Thickness-Steel Through Strain Relief-Steel Stratege-Steel Steel Stee	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout3 (DB, B)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureCable Side (4-40)TerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability Rating-	Number of Positions	25
Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureCable Side (4-40)TerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish-Ingress Protection-Material Flammability Rating-	Number of Rows	2
Mounting TypeFree Hanging (In-Line)Flange FeatureCable Side (4-40)TerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability Rating-	Shell Size, Connector Layout	3 (DB, B)
Flange FeatureCable Side (4-40)TerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability Rating-	Contact Type	Signal
TerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability Rating-	Mounting Type	Free Hanging (In-Line)
FeaturesFeed Through, Strain ReliefShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability Rating-	Flange Feature	Cable Side (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability Rating-	Termination	IDC, Ribbon Cable
Contact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability Rating-	Features	Feed Through, Strain Relief
Contact Finish Thickness-Ingress Protection-Material Flammability Rating-	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability Rating-	Contact Finish	Gold
Material Flammability Rating -	Contact Finish Thickness	-
	Ingress Protection	-
Paport arrors?	Material Flammability Rating	-
Report errors:		Report errors?

8657O25S065TLF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

8657O25S065TLF Payment Methods





If you have any question about 8657O25S065TLF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com