

## 8690780000

#### 8690780000 Information

m	Part Number	8690780000
	Manufacturer	Weidmuller
	Category	Relays Power Relays, Over 2 Amps
	Description	RELAY GEN PURPOSE DPDT 16A 230V
	Package	-
- Salation -		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 8690780000 Specifications

Manufacturer Part Number 869078000   Manufacturer Weidmuller   Category Relays   Package -   Package -   Series RPW   Coll Type General Purpose   Coll Current IO.ImA   Coll Current 0.1mA   Coll Acting Current) JODYC 2 Form C)   Contact Form DPDT (2 Form C)   Contact Rating (Current) 16A   Switching Voltage (Max) 184 VAC - Max   Turn On Voltage (Max) 195 VAC   Querta Time 15ms   Release Time 10ms   Features -   Features Socketable   Furning Type Goketable			
Relays   Power Relays, Over 2 Amps   Package -   Series RPW   Relay Type General Purpose   Coil Type Non Latching   Coil Current 10.1mA   Coil Voltage 230VAC   Contact Form DPDT (2 Form C)   Contact Rating (Current) 16A   Switching Voltage 440VAC - Max   Turn ON Voltage (Max) 184 VAC   Qierat Time 15ms   Release Time -   Release Time -   Mounting Type Socketable   Features -   Features Pug In, Quick Connect - 0.250" (6.3mm)	Manufacturer Part Number	8690780000	
Power Relays, Over 2 AmpsPackage-SeriesRPWRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.1mACoil Voltage230VACContact FormDPDT (2 Form C)Contact Rating (Current)16ASwitching Voltage (Max)184 VACTurn On Voltage (Max)184 VACOperate Time15msRelease Time10msFeatures-Mounting TypeSocketableTermination StyleHug In, Quick Connect - 0.250" (6.3mm)	Manufacturer	Weidmuller	
Package-SeriesRPWRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.1mACoil Voltage230VACContact FormDPDT (2 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)184 VACOperate Time69 VACRelease Time10msFeatures-Mounting TypeSocketablePurg Ling Ling Ling Ling Ling Ling Ling Lin	Category	Relays	
SeriesRPWRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.1mACoil Voltage230VACContact FormDPDT (2 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)184 VACOperate Time15msRelease Time10msFeatures-Mounting TypeSocketableTermination StylePug In, Quick Connect - 0.250" (6.3mm)		Power Relays, Over 2 Amps	
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.1mACoil Voltage230VACContact FormDPDT (2 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)69 VACOperate Time15msRelase Time10msFeatures-Mounting TypeSocketableTermination StyleHug In, Quick Connect - 0.250" (6.3mm)	Package	-	
Coil TypeNon LachingCoil Current10.1mACoil Voltage230VACContact FormDPDT (2 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)184 VACOperate Time69 VACRelease Time15msFeatures-Mounting Type50 KetableTermination Style91 Gu Jack Connect - 0.250" (6.3mm)	Series	RPW	
Coil Current10.1mACoil Voltage230VACContact FormDPDT (2 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)184 VACTurn Off Voltage (Min)69 VACOperate Time15msRelease Time10msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Relay Type	General Purpose	
Coil Voltage230VACContact FormDPDT (2 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)184 VACTurn Off Voltage (Min)69 VACOperate Time15msRelease Times-Features-Mounting TypeSocketableTermination StyleHug In, Quick Connect - 0.250" (6.3mm)	Coil Type	Non Latching	
Contact FormDPDT (2 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)184 VACTurn Off Voltage (Min)69 VACOperate Time15msRelease Time10msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Coil Current	10.1mA	
Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)184 VACTurn Off Voltage (Min)69 VACOperate Time15msRelease Time10msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Coil Voltage	230VAC	
Switching Voltage440VAC - MaxTurn On Voltage (Max)184 VACTurn Off Voltage (Min)69 VACOperate Time15msRelease Time10msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Contact Form	DPDT (2 Form C)	
Turn On Voltage (Max)184 VACTurn Off Voltage (Min)69 VACOperate Time15msRelease Time10msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Contact Rating (Current)	16A	
Turn Off Voltage (Min)69 VACOperate Time15msRelease Time10msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Switching Voltage	440VAC - Max	
Operate Time15msRelease Time10msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Turn On Voltage (Max)	184 VAC	
Release Time10msFeatures-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Turn Off Voltage (Min)	69 VAC	
Features-Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Operate Time	15ms	
Mounting TypeSocketableTermination StylePlug In, Quick Connect - 0.250" (6.3mm)	Release Time	10ms	
Termination StylePlug In, Quick Connect - 0.250" (6.3mm)	Features	-	
	Mounting Type	Socketable	
Report errors?	Termination Style	Plug In, Quick Connect - 0.250" (6.3mm)	
		Report errors?	

#### 8690780000 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## 8690780000 Payment Methods





If you have any question about 8690780000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com