

870025375010

870025375010 Information

www.consener.com	Part Number Manufacturer Category Description Package	870025375010 Wurth Electronics Inc. Capacitors Aluminum - Polymer Capacitors CAP ALUM POLY 820UF 20% 16V T/H Radial, Can	
	Раскаде	For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



870025375010 Specifications

Manufacturer Wurth Electronics Inc. Category Capacitors Aluminum - Polymer Capacitors Aluminum - Polymer Capacitors Package Radial, Can Series WCAP-PTG5 Type Polymer Capacitance 820µF Capacitance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) 12 mOhm Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency 55A @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Size / Dimension 0.551" (14.00mm) Murate Mount Land Size - Mounting Type Through Hole	-	
CategoryCapacitorsAluminum - Polymer CapacitorsPackageRadial, CanPackageKadial, CanSeriesWCAP-PTG5TypePolymerCapacitance820µFColerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency55A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	870025375010
Aluminum - Polymer CapacitorsPackageRadial, CanSeriesWCAP-PTG5TypePolymerCapacitance820µFTolerance±20%Voltage - Rated16∨ESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency5.5A @ 100kHzRipple Current - High Frequency0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension0.551" (14.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Wurth Electronics Inc.
PackageRadial, CanSeriesWCAP-PTG5TypePolymerCapacitance820μFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency5.5A @ 100kHzRipple Current - High Frequency0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesWCAP-PTG5TypePolymerCapacitance820µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency5.5A @ 100kHzInpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Package / CaseRadial, Can		Aluminum - Polymer Capacitors
TypePolymerCapacitance820µFCopacitance±20%Voltage - Rated16VESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency55A @ 100kHzInpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseRidial, Can	Package	Radial, Can
Capacitance20µFCapacitance±20%Tolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency275mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Series	WCAP-PTG5
Tolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency275mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Туре	Polymer
Voltage - Rated16VESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency275mA @ 120HzBipple Current - High Frequency5.5A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.551" (14.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Package / CaseRatial, Can	Capacitance	820µF
ESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency275mA @ 120HzBipple Current - High Frequency5.5A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency275mA @ 120HzRipple Current - High Frequency5.5A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	16V
Operating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency275mA @ 120HzRipple Current - High Frequency5.5A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	12 mOhm
ApplicationsGeneral PurposeRipple Current - Low Frequency275mA @ 120HzRipple Current - High Frequency5.5A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Ripple Current - Low Frequency275mA @ 120HzRipple Current - High Frequency5.5A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - High Frequency5.5A @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	275mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	5.5A @ 100kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.551" (14.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

870025375010 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

870025375010 Payment Methods



870025375010 Shipping Methods



If you have any question about 870025375010, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com