

### 87606-338LF Information

Heisener.com

For Reference Only

**Part Number** 87606-338LF **Manufacturer** Amphenol FCI

**Category** Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** CONN RCPT 76POS .100" DBL PCB

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 87606-338LF Specifications

Manufacturer Part Number       87606-338LF         Manufacturer       Amphenol FCI         Category       Connectors, Interconnects         Rectangular Connectors - Headers, Receptacles, Female Sockets         Package       -         Series       Dubox?         Connector Type       Receptacle         Contact Type       Female Socket         Style       Board to Board         Number of Positions       76         Number of Positions Loaded       All         Pitch - Mating       0.100" (2.54mm)         Number of Rows       2         Row Spacing - Mating       0.100" (2.54mm)         Mounting Type       Through Hole         Termination       Solder         Fastening Type       Push-Pull         Contact Finish - Mating       Gold         Contact Finish - Thickness - Mating       30µin (0.76µm)         Insulation Color       Blue	•	
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets  Package - Series Dubox? Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions 76 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating Mounting Type Through Hole Termination Fastening Type Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Blue	Manufacturer Part Number	87606-338LF
Rectangular Connectors - Headers, Receptacles, Female Sockets  Package  Series  Dubox?  Connector Type  Receptacle  Contact Type  Female Socket  Style  Board to Board  Number of Positions  76  Number of Positions Loaded  Pitch - Mating  Number of Rows  2  Row Spacing - Mating  Mounting Type  Through Hole  Termination  Fastening Type  Contact Finish - Mating  Gold  Contact Finish Thickness - Mating  Jubox?  Receptacles, Female Socket  Package	Manufacturer	Amphenol FCI
Package-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions76Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlue	Category	Connectors, Interconnects
SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions76Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlue		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions 76 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Insulation Color Blue	Package	-
Contact Type Style Board to Board Number of Positions 76 Number of Positions Loaded Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Blue	Series	Dubox?
StyleBoard to BoardNumber of Positions76Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlue	Connector Type	Receptacle
Number of Positions76Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlue	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlue	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlue	Number of Positions	76
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlue	Number of Positions Loaded	All
Row Spacing - Mating       0.100" (2.54mm)         Mounting Type       Through Hole         Termination       Solder         Fastening Type       Push-Pull         Contact Finish - Mating       Gold         Contact Finish Thickness - Mating       30μin (0.76μm)         Insulation Color       Blue	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlue	Number of Rows	2
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30μin (0.76μm) Insulation Color Blue	Row Spacing - Mating	0.100" (2.54mm)
Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating 30μin (0.76μm) Insulation Color Blue	Mounting Type	Through Hole
Contact Finish - Mating Gold Contact Finish Thickness - Mating 30μin (0.76μm) Insulation Color Blue	Termination	Solder
Contact Finish Thickness - Mating 30μin (0.76μm) Insulation Color Blue	Fastening Type	Push-Pull
Insulation Color Blue	Contact Finish - Mating	Gold
	Contact Finish Thickness - Mating	30μin (0.76μm)
0.00511/0.51	Insulation Color	Blue
Insulation Height 0.335" (8.51mm)	Insulation Height	0.335" (8.51mm)
Contact Length - Post 0.114" (2.90mm)	Contact Length - Post	0.114" (2.90mm)
Operating Temperature -	Operating Temperature	-
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	9.54mm
Ingress Protection	-
Features	-
	Report errors?

#### 87606-338LF Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 87606-338LF Payment Methods



















## 87606-338LF Shipping Methods













If you have any question about 87606-338LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com