


885012209009

Request a Quote

885012209009 Information

www.halanner.com	Part Number	885012209009
	Manufacturer	Wurth Electronics Inc.
	Category	Capacitors Ceramic Capacitors
	Description	CAP CER 0.47UF 16V X7R 1210
	Package	1210 (3225 Metric)
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



885012209009 Specifications

ManufacturerWurth Electronics Inc.CapacitorsCapacitorsPackage1210 (3225 Metric)SeriesWCAP-CSGPCapacitance0.47μFTolerance±10%Voltage - Rated16VTomperature Coefficient55°C ~ 125°CPactangs-Ratings-ApplicationsGeneral PurposeFailure Rate-ApplicationsSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126° L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Spacing-Lead Spacing-Starten Starten Starte	_	
CaegoryCapacitorsPackage1210 (3225 Metric)Package1210 (3225 Metric)SeriesWCAP-CSGPCapacitance0.47µFTolerance±10%Voltage - Rated16VOperating Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CPatters-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.41" (1.05mm)Lead Spleie-Lead Spleie-Lead Spleie-Carter Spleie-Carter Spleie-Stare Spleie-S	Manufacturer Part Number	885012209009
Ceramic CapacitorsPackage1210 (3225 Metric)SeriesWCAP-CSGPCapacitance0.47μFTolerance±10%Voltage - Rated16VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.42° L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.41" (1.05mm)Lead Style-Lead Style-	Manufacturer	Wurth Electronics Inc.
Package1210 (3225 Metric)SeriesWCAP-CSGPCapacitance0.47μFTolerance±10%Voltage - Rated16VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126° L x 0.098° W (3.20mm x 2.50mm)Height - Seated (Max)-Lead Spacing-Lead Style-	Category	Capacitors
NoteWCAP-CSGPCapacitance0.47μFTolerance±10%Voltage - Rated16VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.041" (1.05mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance0.47µFTolerance±10%Voltage - Rated16VYoltage - Rated16VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.421° (1.05mm) x 0.50mm x 2.50mm)Height - Seated (Max)-Lead Spacing-Lead Style-	Package	1210 (3225 Metric)
Tolerance±10%Voltage - Rated16VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.041" (1.05mm)Lead Style-	Series	WCAP-CSGP
Voltage - Rated16VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Lead Spacing0.041" (1.05mm)Lead Style-	Capacitance	0.47µF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.041" (1.05mm)Lead Spacing-Lead Style-	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.041" (1.05mm)Lead Spacing-Lead Style-	Voltage - Rated	16V
Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.041" (1.05mm)Lead Spacing-Lead Style-	Temperature Coefficient	X7R
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.041" (1.05mm)Lead Spacing-Height - Seated (Max)-	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.041" (1.05mm)Lead Spacing-Lead Style-	Features	-
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.041" (1.05mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.041" (1.05mm)Lead Spacing-Lead Style-	Applications	General Purpose
Package / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)-Thickness (Max)0.041" (1.05mm)Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm) Height - Seated (Max) - Thickness (Max) 0.041" (1.05mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.041" (1.05mm)Lead Spacing-Lead Style-	Package / Case	1210 (3225 Metric)
Thickness (Max)0.041" (1.05mm)Lead Spacing-Lead Style-	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.041" (1.05mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

E-mail: salesdept@heisener.com

885012209009 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

885012209009 Payment Methods





If you have any question about 885012209009, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com