

# 885362211011

### 885362211011 Information

www.theseurr.com	Part Number Manufacturer Category Description Package	885362211011 Wurth Electronics Inc. Capacitors Ceramic Capacitors CAP CER 1000PF 250VAC X7R 1812 1812 (4532 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 885362211011 Specifications

ManufacturerWurth Electronics Inc.CapacitorsCapacitorsPackageI812 (4532 Metric)SeriesWCAP-CSSACapacitance1000pFTolerance±10%Voltage - Rated250VACOperating Temperature Coefficient55°C ~ 125°CPactangs-RatingsSafetyApplicationsSafetyFailure Rate-Package / Case1812 (4532 Metric)Synther SupportSafetyFailure Rate-Package / Case1812 (4532 Metric)Size / Dimension0.171" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Spacing-Stafe S	_	
CaegoryCapacitorsPackage1812 (4532 Metric)Package1812 (4532 Metric)SeriesWCAP-CSSACapacitance1000pFTolerance±10%Voltage - Rated250VACOperating Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsSafetyApplicationsSafetyFailure Rate-Mounting TypeSuface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.171" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.071" (1.80mm)Lead Spleie-	Manufacturer Part Number	885362211011
Ceramic CapacitorsPackage1812 (4532 Metric)SeriesWCAP-CSSACapacitance1000pFTolerance±10%Voltage - Rated250VACTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.017" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.071" (1.80mm)Lead Style-	Manufacturer	Wurth Electronics Inc.
Package1812 (4532 Metric)SeriesWCAP-CSSACapacitance1000pFTolerance±10%Voltage - Rated250VACTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case.117" L x 0.126" W (4.50mm x 3.20mm)Bieght - Seated (Max).071" (1.80mm)Lead Spacing-Lead Style-	Category	Capacitors
SeriesWCAP-CSSACapacitance1000pFTolerance±10%Voltage - Rated250VACTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.071" (1.80mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance1000pFTolerance±10%Voltage - Rated250VACTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting Type1812 (4532 Metric)Size / Dimension0.717" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.071" (1.80mm)Lead Spacing-Lead Style-	Package	1812 (4532 Metric)
Tolerance     ±10%       Voltage - Rated     250VAC       Temperature Coefficient     X7R       Operating Temperature     -55°C ~ 125°C       Features     -       Ratings     X2, Y3       Applications     Safety       Failure Rate     -       Mounting Type     Surface Mount, MLCC       Package / Case     1812 (4532 Metric)       Size / Dimension     0.177" L x 0.126" W (4.50mm x 3.20mm)       Height - Seated (Max)     -       Thickness (Max)     0.071" (1.80mm)       Lead Style     -	Series	WCAP-CSSA
Voltage - Rated250VACTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Capacitance	1000pF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.071" (1.80mm)Lead Spacing-Lead Style-	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.071" (1.80mm)Lead Spacing-Lead Style-	Voltage - Rated	250VAC
Features-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.071" (1.80mm)Lead Spacing-Lead Style-	Temperature Coefficient	X7R
RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.071" (1.80mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.071" (1.80mm)Lead Spacing-Lead Style-	Features	-
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.071" (1.80mm)Lead Spacing-Lead Style-	Ratings	X2, Y3
Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.071" (1.80mm)Lead Spacing-Lead Style-	Applications	Safety
Package / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.071" (1.80mm)Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension   0.177" L x 0.126" W (4.50mm x 3.20mm)     Height - Seated (Max)   -     Thickness (Max)   0.071" (1.80mm)     Lead Spacing   -     Lead Style   -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.071" (1.80mm)Lead Spacing-Lead Style-	Package / Case	1812 (4532 Metric)
Thickness (Max)0.071" (1.80mm)Lead Spacing-Lead Style-	Size / Dimension	0.177" L x 0.126" W (4.50mm x 3.20mm)
Lead Spacing -   Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.071" (1.80mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### 885362211011 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 885362211011 Payment Methods



## 885362211011 Shipping Methods



If you have any question about 885362211011, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com