

885362211015

equest a Quote

885362211015 Information

Part Number	885362211015
Manufacturer	Wurth Electronics Inc.
Category	Capacitors Ceramic Capacitors
Description	CAP CER 2200PF 250VAC X7R 1812
Package	1812 (4532 Metric)
	For the pricing/inventory/lead time, please contact us
	Website: https://www.heisener.com E-mail: salesdept@heisener.com
	Manufacturer Category Description

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



885362211015 Specifications

ManufacturerWurh Electronics Inc.CapacitorsCapacitorsPackageI812 (4532 Metric)SeriesWCAP-CSSACapacitance2200pFTolerance±10%Voltage - Rated250VACOperating Temperature Coefficient×7RSeries-RatingsSafetyApplicationsSafetyFailure Rate-Package / CaseI812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Size / Dimension0.110" (2.80mm)Lead Spacing-Lead Spacing <td< th=""><th>_</th><th></th></td<>	_	
CaegoryCapacitorsPackage1812 (4532 Metric)Package1812 (4532 Metric)SeriesWCAP-CSSACapacitance2200pFTolerance±10%Voltage - Rated250VACOperating Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsSafetyApplicationsSafetyFailure Rate-Mounting TypeSuface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Syle-	Manufacturer Part Number	885362211015
Ceramic CapacitorsPackage1812 (4532 Metric)SeriesWCAP-CSSACapacitance2200pFTolerance±10%Voltage - Rated250VACTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Style-	Manufacturer	Wurth Electronics Inc.
Package1812 (4532 Metric)SeriesWCAP-CSSACapacitance2200pFTolerance±10%Voltage - Rated250VACTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case.117" L x 0.126" W (4.50mm x 3.20mm)Bieght - Seated (Max)-Thickness (Max).110" (2.80mm)Lead Spacing-Lead Style-	Category	Capacitors
SeriesWCAP-CSSACapacitance2200pFTolerance±10%Voltage - Rated250VACTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance2200pFTolerance±10%Voltage - Rated250VACTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Nounting Type1812 (4532 Metric)Size / Dimension0.110" (2.80mm) x 3.20mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Package	1812 (4532 Metric)
Tolerance±10%Voltage - Rated250VACTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.110" (2.80mm)Height - Seated (Max)-Lead Style-	Series	WCAP-CSSA
Voltage - Rated250VACTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Lead Spacing-Lead Style-	Capacitance	2200pF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Spacing-Lead Style-	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Spacing-Lead Style-	Voltage - Rated	250VAC
Features-RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Spacing-Lead Style-	Temperature Coefficient	X7R
RatingsX2, Y3ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsSafetyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Spacing-Lead Style-	Features	-
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Spacing-Lead Style-	Ratings	X2, Y3
Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Spacing-Lead Style-	Applications	Safety
Package / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.110" (2.80mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.110" (2.80mm)Lead Spacing-Lead Style-	Package / Case	1812 (4532 Metric)
Thickness (Max)0.110" (2.80mm)Lead Spacing-Lead Style-	Size / Dimension	0.177" L x 0.126" W (4.50mm x 3.20mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.110" (2.80mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

885362211015 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

885362211015 Payment Methods





If you have any question about 885362211015, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com