

8869860000 Information



For Reference Only

Part Number 8869860000 Manufacturer Weidmuller Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 16A 230V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









8869860000 Specifications

Manufacturer Part Number8869860000ManufacturerWeidmullerCategoryRelays Power Relays, Over 2 AmpsPackage-SeriesRCIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current3.2mACoil Voltage230VACContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage250VAC - MaxTurn On Voltage (Max)172.5 VACTurn Off Voltage (Min)34.5 VACOperate Time7msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRCIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current3.2mACoil Voltage230VACContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage250VAC - MaxTurn On Voltage (Max)172.5 VACTurn Off Voltage (Min)34.5 VACOperate Time7msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	8869860000
Package - Series RCI Relay Type General Purpose Coil Type Non Latching Coil Current 3.2mA Coil Voltage 230VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 250VAC - Max Turn On Voltage (Max) 172.5 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole Termination Style Purpose RCI	Manufacturer	Weidmuller
Package-SeriesRCIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current3.2mACoil Voltage230VACContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage250VAC - MaxTurn On Voltage (Max)172.5 VACTurn Off Voltage (Min)34.5 VACOperate Time7msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesRCIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current3.2mACoil Voltage230VACContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage250VAC - MaxTurn On Voltage (Max)172.5 VACTurn Off Voltage (Min)34.5 VACOperate Time7msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current3.2mACoil Voltage230VACContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage250VAC - MaxTurn On Voltage (Max)172.5 VACTurn Off Voltage (Min)34.5 VACOperate Time7msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current3.2mACoil Voltage230VACContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage250VAC - MaxTurn On Voltage (Max)172.5 VACTurn Off Voltage (Min)34.5 VACOperate Time7msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	RCI
Coil Current 3.2mA Coil Voltage 230VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 250VAC - Max Turn On Voltage (Max) 172.5 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 230VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 250VAC - Max Turn On Voltage (Max) 172.5 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 172.5 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole Termination Style	Coil Current	3.2mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 172.5 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole Termination Style	Coil Voltage	230VAC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 172.5 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Sms Features Mounting Type Through Hole Termination Style 172.5 VAC 7ms 34.5 VAC 7ms 7ms Through Hole PC Pin	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole Termination Style 7es	Switching Voltage	250VAC - Max
Operate Time 7ms Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	172.5 VAC
Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	34.5 VAC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	7ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	3ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

8869860000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

8869860000 Payment Methods





















8869860000 Shipping Methods













If you have any question about 8869860000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com