

## **8869900000 Information**



For Reference Only

Part Number 8869900000
Manufacturer Weidmuller
Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 8A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 8869900000 Specifications

Manufacturer Part Number886990000ManufacturerWeidmullerCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRCIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.7mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage250VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time7msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRCIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.7 mACoil Voltage48 VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage250 VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time7 msRelease Time2 msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	8869900000
Package - Series RCI Relay Type General Purpose Coil Type Non Latching Coil Current 8.7mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 7ms Release Time 2ms Features - Mounting Type Through Hole Termination Style Purpose RCI RCI RCI RCI RCI RCI RCI AND R	Manufacturer	Weidmuller
Package - Series RCI Relay Type General Purpose Coil Type Non Latching Coil Current 8.7mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 7ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesRCIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.7mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage250VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time7msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.7mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage250VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time7msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current8.7mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage250VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time7msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	RCI
Coil Current 8.7mA  Coil Voltage 48VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 8A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 33.6 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 7ms  Release Time 2ms  Features  Mounting Type Through Hole  Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 250VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 7ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current) 8A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 33.6 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 7ms  Release Time 2ms  Features -  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	8.7mA
Contact Rating (Current)  Switching Voltage  250VAC - Max  Turn On Voltage (Max)  33.6 VDC  Turn Off Voltage (Min)  4.8 VDC  Operate Time  7ms  Release Time  2ms  Features  -  Mounting Type  Through Hole  Termination Style	Coil Voltage	48VDC
Switching Voltage 250VAC - Max  Turn On Voltage (Max) 33.6 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 7ms  Release Time 2ms  Features -  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  2ms  Features  Mounting Type  Through Hole  Termination Style  33.6 VDC	Contact Rating (Current)	8A
Turn Off Voltage (Min)  Operate Time  7ms  Release Time  2ms  Features  -  Mounting Type  Through Hole  Termination Style  4.8 VDC  7ms  7ms  2ms  PC Pin	Switching Voltage	250VAC - Max
Operate Time 7ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	33.6 VDC
Release Time 2ms  Features -  Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	4.8 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	7ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	2ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **8869900000 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 8869900000 Payment Methods



















## 8869900000 Shipping Methods













If you have any question about 8869900000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com