

89450231 Information

Heisener.com

Part Number 89450231
Manufacturer Crouzet

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 150W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









90450231	Specifications
89450231	Specifications

Manufacturer Part Number 89450231 Manufacturer Crouzet Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Millenium Supply, 89450 Type Linear Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.2A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Millenium Supply, 89450 Type Linear Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.2A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Manufacturer Part Number	89450231
Package - Series Millenium Supply, 89450 Type Linear Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.2A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Manufacturer	Crouzet
Package - Series Millenium Supply, 89450 Type Linear Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.2A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series Millenium Supply, 89450 Type Linear Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.2A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)		AC DC Converters
Type Linear Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.2A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Package	-
Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.2A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Series	Millenium Supply, 89450
Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.2A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Туре	Linear
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Site / Dimension 24V 24V 24V 24V 24V - Current - Output (Max) - Current - Output (Max) 6.2A Power (Watts) 150W ITE (Commercial) 3kV (3000V) Corrent - Oo'C (With Derating) Features Universal Input Chassis Mount 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Size / Dimension - Operating Type Size / Dimension - Current - Output (Max) - Current - Output (Max) 6.2A - Current - Output (Max) 6.2A - Current - Output (Max) 6.2A - ITE (Commercial) Siv (3000V) - Commercial) Voltage - Isolation 3kV (3000V) - Commercial) Siv (3000V) - Commercial) Voltage - Isolation 3kV (3000V) - Chossis Mount 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Voltage - Input	230VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Sifficiency Operating Temperature O°C ~ 60°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) 6.2A ITE (Commercial) Size / Dimension O°C ~ 60°C (With Derating) Chassis Mount 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) 6.2A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Voltage - Output 2	-
Current - Output (Max) 6.2A Power (Watts) 150W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount 5ize / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Current - Output (Max)	6.2A
Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Power (Watts)	150W
Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Applications	ITE (Commercial)
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension $7.87^{\circ}\text{L} \times 3.86^{\circ}\text{W} \times 1.97^{\circ}\text{H}$ (200.0mm x 98.0mm x 50.0mm)	Voltage - Isolation	3kV (3000V)
Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Efficiency	-
Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating)
Size / Dimension 7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)	Features	Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.87" L x 3.86" W x 1.97" H (200.0mm x 98.0mm x 50.0mm)
		Report errors?

89450231 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

89450231 Payment Methods



















89450231 Shipping Methods













If you have any question about 89450231, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com